

MOMENTO LIMEWASH EFFECT is a water-based decorative coating specially formulated to recreate the soft, mottled, and natural appearance of traditional limewash finishes — without the limitations of mineral-based systems. It offers a matte, velvety finish with subtle tonal variations, ideal for achieving rustic or aged wall effects.

GENERAL INFORMATION

Paint Type	Water Based, Interior
Binder Type	Acrylic emulsion
Colour	As per colour card
Finishing	Matt
Density	1.28 ± 2% Kg/L
Solid Content	45.0 ± 2 % by weight
Packaging	1L
Storage	Store in a tightly sealed packaging in a cool dry place, away from heat source or ignition
Shelf Life	Up to 24 months in a tightly sealed packaging with the above-mentioned storage conditions

FEATURES

- Authentic limewash aesthetic
- Non-mineral, acrylic-based formula for improved durability
- Good adhesion on primed surfaces
- Easy to apply by sponge for artistic effects
- Suitable for interior applications
- Low VOC
- Low Odour
- Mould & Fungus resistant
- Free from alkylphenol ethoxylate (APEO) & formaldehyde
- Does not contain lead, mercury & heavy metals

USES

- Decorative coating for internal masonry surfaces, such as cement, plastered walls, brickwork and fibre boards.

APPLICATION DATA

Method	1. Apply with sponge in random sweeping strokes to create a limewash texture. 2. Apply 1-2 coats for the desired depth and variation. 3. For a softer, washed-out appearance, dilute slightly with clean water.
Theoretical Coverage	~100 m ² / litre Depending on surface texture, substrate porosity and method of application
Dilution	Max 5% dilution with water
Precaution	Stir product well before use. Do not dilute or mix solvent other than that of manufacturer's instructions. Do not apply in air and substrate temperature below 5°C.

DRYING TIME

Touch Dry	30 minutes at 30 °C
Hard Dry	1 hour max at 30 °C
Overcoating	1 hour minimum based on normal conditions

RECOMMENDED PAINTING SYSTEM

- 1 coat of ***Odour-less Ultra 5102 Sealer***
- 2 coats of ***Vinilex 5000 (color as recommended in color card)***
- 1-2 coats of ***Momento Limewash Effect***

SURFACE PREPARATION

Ensure surface is clean, dry and stable using the following suggested surface treatments:

- **Moisture:** There must not be any water residue on the surface of the substrate. Moisture must be <4% (Sovereign moisture master) before application
- **Unstable matter:** Remove loose bonding film, dirt, peeling paint, etc by high-pressure water jet wash or mechanical means such as power brush or scraper, whichever is suitable
- **Contaminants:** Remove dust and foreign matter by cleaning with damp cloth. Remove oil or grease using solvent or mild detergent. Allow surface to dry
- **Fungus and Algae:** Wash the affected area to remove unstable matters and micro-organisms. Apply Anti-Fungus Solution and leave on for at least 2 hours
- **Hairline cracks:** Fill cracks with suitable exterior grade water-resistant putty or filler

CLEANING INSTRUCTIONS

All equipment should be cleaned with water immediately after use

SAFETY INFORMATION

Before using this product, always read the safety information on the packaging and in the Safety Data Sheet (SDS).

- **Ventilation:** Ensure good ventilation during application and drying to minimize inhalation of vapors or spray mist.
- **Personal Protection:** Avoid direct contact with skin and eyes. Wear suitable personal protective equipment (PPE) such as gloves, goggles, and, if spraying, a respirator.
- **First Aid:** If paint contacts skin, wash immediately with soap and water. If it enters the eyes, rinse thoroughly with clean water and seek medical attention.
- **Fire Safety:** For solvent-based or flammable products, keep away from naked flames, sparks, welding operations, and smoking areas.
- **Spillage:** Clean up spills promptly using appropriate cleaning agents.
- **Suitability:** If unsure about the product's application or compatibility, consult the manufacturer for guidance.

DISCLAIMER

The information in this data sheet is given to the best of Nippon Paint's knowledge and practical experience. Users may consult with Nippon Paint on the general suitability of the product for their needs and specific application practices though it remains each user's responsibility to determine the suitability of the product for the user's particular use. The condition of the substrate and application are not within Nippon Paint's control. Therefore, no implied conditions, warranties or other terms will apply to the product. Nippon Paint does not and cannot warrant the results which the user may obtain by using the product. In no event will Nippon Paint be liable to the user for any kind of loss (whether direct or indirect) even if Nippon Paint was previously advised of it. In line with Nippon Paint's policy for continuous development, Nippon Paint reserves the right to modify the product and the information in this data sheet without prior notice. It is the user's responsibility to check with Nippon Paint for the latest version of this data sheet. This data sheet has been translated into various languages. In the event of any inconsistency, the English version shall prevail.

Customer Service 6265 5355 (Main Line)

www.nipponpaint.com.sg