

TECHNICAL DATA SHEET FOR
SUPER LITEX EMULSION

DESCRIPTION	:	Super Litex Emulsion is a quality and economical paint formulated to decorate and protect all kinds of masonry surfaces for interior walls and ceilings.
TYPE	:	Modified Vinyl Acrylic Copolymer Emulsion
COLOUR	:	White
FINISH	:	Matt
USES	:	Ideally suited for internal aged masonry surfaces such as: <ul style="list-style-type: none">• Cement Plaster• Fibre Boards• Brickworks• Primed Wood• Soft Boards
FEATURES	:	<ul style="list-style-type: none">• Economical• Easy application• Good coverage and hiding power• Anti-fungus property

APPLICATION DATA

METHOD	:	Roller or brush
THEORETICAL COVERAGE	:	Approx. 11 m ² / litre (30 microns DFT)
DILUTION	:	Use clean water. Roller or brush, 10% maximum
SURFACE PREPARATION	:	Ensure surface is clean, dry and stable using the following suggested surface treatments: <ul style="list-style-type: none">• Moisture :There must not be any water residue on the surface of the substrate. Moisture must be <4% (Sovereign moisture master) before application• Unstable matter :Remove loose bonding film, dirt, peeling paint, etc by high-pressure water jet wash or mechanical means such as power brush or scraper, whichever is suitable• Contaminants :Remove dust and foreign matter by cleaning with damp cloth. Remove oil or grease using solvent or mild detergent. Allow surface to dry

SUPER LITEX EMULSION

- **Fungus and Algae** :Wash the affected area to remove unstable matters and micro-organisms. Apply Anti-Fungus Solution and leave on for at least 2 hours
- **Hairline cracks** :Fill cracks with suitable exterior grade water-resistant putty or filler

DRYING TIME	:	Touch Dry - 30 minutes at 30°C
OVERCOATING TIME	:	2 hours based on normal conditions
CLEANING	:	All equipment should be cleaned with water immediately after use.

GENERAL INFORMATION

SOLID CONTENT	:	54.0 ± 2% by weight
SPECIFIC GRAVITY	:	1.49 ± 3% kg/litre
PACKING	:	25 kg
STORAGE	:	Store in a tightly sealed container in a cool dry place.
SHELF LIFE	:	Up to 24 months in a tightly sealed container.
PRECAUTION	:	Avoid direct contact with sensitive skin. Use appropriate personal protective equipment.

Refer to the product Safety Data Sheet for more information.

The information given is intended to give a description of the product performance under specific test conditions. Nevertheless, we cannot assume any responsibility for the use of it since circumstances under which the products are applied in practice are subjected to many variations. We reserve the right to alter the given data without notice.

Enquiries / Contact Details	:	Customer Service 6265 5355 (Main Line) 6264 1603 (Fax) www.nipponpaint.com.sg
------------------------------------	---	--