

# **SAFETY DATA SHEET**

SDS Number: SDS-71040 Version No: 003

Revision Date/Version No:19-08-2024 /3/1.1.1

# 1. IDENTIFICATION OF THE SUBSTANCE / MIXTURE AND OF THE COMPANY / UNDERTAKING

Product Name: AQUA EPOXY WALLCOAT
Intended Use: Water-Based Decorative Paint
Manufacturer: Nippon Paint (S) Co. Pte Ltd

Nippon Paint (S) Co. Pte Ltd No. 1 First Lok Yang Road

Jurong Singapore 629728 (65) 6 265 5355

Emergency Phone Number: (65) 6 265 5355 Fax Numbers: (65) 6 264 1603

# 2. HAZARDS IDENTIFICATION

#### **GHS Classification:**

## **Physical Hazard**

Not classified as a physical hazard under GHS criteria

# **Health Hazard**

Skin corrosion/irritation Category 2
Skin sensitization Category 1

Specific target organ toxicity:

- Repeated exposure Category 1

## **Environmental Hazard**

Not classified as an environmental hazard under GHS criteria

## **GHS Pictogram**



# Signal Word

Danger

# **Hazard statements**

H315: Causes skin irritation

H317: May cause an allergic skin reaction

H372: Causes damage to organs through prolonged or repeated exposure

# **Precautionary statements**

P260: Do not breathe dust/fume/gas/mist/vapours/spray

P261: Avoid breathing dust/fume/gas/mist/vapours/spray

P264: Wash hands thoroughly after handling

P270: Do not eat, drink or smoke when using this product

P272: Contaminated work clothing should not be allowed out of the workplace

P280: Wear protective gloves/protective clothing/eye protection/face protection

#### Response

P314: Get medical advice/attention if you feel unwell

P321: Specific treatment (see Section 4 of SDS)

P362: Take off contaminated clothing and wash before reuse

P363: Wash contaminated clothing before reuse

P302+352: IF ON SKIN: Wash with soap and water

P332+313: If skin irritation occurs: Get medical advice/attention

P333+313: If skin irritation or a rash occurs: Get medical advice/attention

## Storage

None

## Disposal

P501: Dispose of contents/container to appropriate waste site or reclaimer in accordance with local or national regulations

# 3. COMPOSITION / INFORMATION ON INGREDIENTS

Substances	CAS No.	%
Crystalline Silica	14808-60-7	5-12
Phenol, 4.4'-(1-methylethylidene) bis-, polymer with N,N'-bis(2-aminoethyl)-1,2-ethanediamine and (chloromethyl) oxirane	38294-69-8	2-4
Substances determined to be non-hazardous	-	Balance
		100%

## 4. FIRST-AID MEASURES

## **INHALATION**

- Move person to fresh air and call for medical assistance immediately.
- If not breathing, give artificial respiration, if breathing is difficult, give oxygen. Keep at rest.

## **SKIN CONTACT**

- In case of contact, immediately flush skin with large amounts of water and soap while removing contaminated clothing and shoes.
- o If irritation persists, get medical attention.

## **EYE CONTACT**

- Immediately flush eyes with large amounts of water until irritation subsides.
- · Remove contact lens.
- o Obtain medical attention, preferably by an ophthalmologist, immediately.

## **INGESTION**

 DO NOT induce vomiting unless directed to do so by a medical personnel. Never give anything by mouth to an unconscious person. Keep at rest. Get medical attention immediately.

# 5. FIRE FIGHTING MEASURES

#### SUITABLE FIRE EXTINGUISHING MEDIA

Alcohol - resistant foam, Carbon dioxide, or dry chemical type.

#### SPECIFIC HAZARDS ARISING FROM THE CHEMICAL

 Combustion products may include and are not limited to: Carbon monoxide and Carbon dioxide.

#### SPECIAL PROTECTIVE ACTIONS FOR FIRE FIGHTERS

- Wear full protective clothing and NIOSH approved self contained breathing apparatus.
- Use water spray to cool fire exposed surfaces and to protect personnel. If a leak or spill has not ignited, use water spray to disperse the vapours.
- If possible, isolate product from heat, electrical equipments, sparks and open flames.
- Avoid spraying water directly into storage containers.
- Closed containers may explode when exposed to extreme heat.
- o Avoid spreading burning liquid with water, isolate liquid.
- o Do not allow runoff from fire fighting to enter drains or watercourses.

## 6. ACCIDENTAL RELEASE MEASURES

## PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT AND EMERGENCY PROCEDURE

- Wear appropriate protective equipment, e.g. respirators, eye protection, gloves and safety shoes.
- Avoid substance contact with eyes. Do not inhale vapours.
- Ensure supply of fresh air in enclosed rooms.

#### **ENVIRONMENTAL PRECAUTIONS**

- Eliminate sources of ignition.
- Keep public away.
- o Contain spilled liquid with sand or other non-combustible absorbent materials.
- Wash area and prevent runoff into drains and sewerage system.
- Advise authorities if substance has entered a watercourse or sewer or has contaminated soil or vegetation.

#### METHODS AND MATERIALS FOR CONTAINMENTS AND CLEANING UP

- Clean up all spills immediately.
- Absorb spill with absorbent and inert material, then place in container.
- Disposal in accordance to local/national regulations.

# 7. HANDLING AND STORAGE

#### PRECAUTIONS FOR SAFE HANDLING

- Use appropriate personal protective equipment.
- Keep out of reach of children.
- Handle containers with care. Open slowly in order to control possible pressure release.
- Do not pressurize containers.
- o Do not ingest. Do not breathe in gas/fumes/vapour. Avoid contact with skin and eyes.
- For personal protection, see section 8.

- Use only in areas from which all naked lights and other sources of ignition have been excluded.
- Take precautionary measures against static discharge.
- Protect from frost and extremes of temperature.

#### CONDITIONS FOR SAFE STORAGE, INCLUDING ANY INCOMPATIBILTIES

- Keep containers tightly closed.
- Containers that are opened should be properly resealed and kept upright to prevent leakage.
- Store in cool, dry and well ventilated place at temperature between 20°C to 40°C away from heat and sources of ignition.

# 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

#### **CONTROL PARAMETERS/OCCUPATIONAL LIMITS**

Substances	ACGIH TLV-TWA		OSHA PEL-TWA	
	ppm	mg/m3	ppm	mg/m3
Crystalline Silica	-	0.03	-	0.50
Phenol, 4.4'-(1-methylethylidene) bis-, polymer with	-	-	-	-
N,N'-bis(2-aminoethyl)-1,2-ethanediamine and				
(chloromethyl) oxirane				

#### APPROPRIATE ENGINEERING CONTROL MEASURES

- Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapours below their respective occupational exposure limits.
- Ensure eyewash stations and safety showers are close to the workstation location.

#### PERSONAL PROTECTION

Respiratory Protection: Based on the local regulation, risk assessment of hazards and potential

exposure, use of NIOSH - approved respirators if necessary.

Hand Protection: Use of solvent resistance type or chemical resistant type of protective gloves

is recommended.

Eye Protection: Use of safety glasses or goggles with side shields is recommended.

Skin / Body Protection: Wear chemical resistant clothes and safety shoes when handling product.

# 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : Liquid

Odour : Mild paint odour Odour threshold : Not available

pH : 8-10

Melting point/freezing point : Not available Initial boiling point and boiling range : Not available Flash point : Not available Evaporation rate : Not available Flammability (solid, gas) : Not applicable Lower flammability or explosive limit : Not available Upper flammability or explosive limit : Not available : Not available Vapour pressure : Not available Vapour density : Not available Relative density

Solubility : Miscible in water
Partition coefficient : Not available
Auto-ignition temperature : Not available
Decomposition temperature : Not available
Viscosity : 93 - 103 KU

# 10. STABILITY AND REACTIVITY

#### REACTIVITY

No dangerous reaction known under condition of normal use.

#### **CHEMICAL STABILITY**

• The product is stable under recommended storage and handling conditions. (see section 7)

#### POSSIBILITY OF HAZARDOUS REACTION

Under normal conditions of storage and use, hazardous reaction will not occur.

#### **CONDITIONS TO AVOID**

 Keep away from oxidising agents, strongly alkaline and strongly acidic materials in order to avoid exothermic reactions. Avoid all possible sources of ignition (spark or flame). Do not pressurize, cut, weld, braze, drill, grind or expose containers to heat or sources of ignition.

#### HAZARDOUS DECOMPOSITION PRODUCTS

 When exposed to high temperatures may produce hazardous decomposition products such as carbon monoxide, carbon dioxide, oxides of nitrogen and smoke.

# 11. TOXICOLOGICAL INFORMATION

There is no data available on the product itself.

Toxicological information of substances:

#### Acute oral toxicity

Harmful if swallowed

<u>Substances</u> <u>Oral LD50(Rat), mg/kg</u> Crystalline Silica <u>Data not available</u>

Phenol, 4.4'-(1-methylethylidene) bis-, polymer 300 with N,N'-bis(2-aminoethyl)-1,2-ethanediamine

and (chloromethyl) oxirane

## Acute dermal/skin toxicity

May be harmful if in contact with skin

<u>Substances</u> <u>Dermal LD50 (Rabbit), mg/kg</u>

Crystalline Silica Data not available Phenol, 4.4'-(1-methylethylidene) bis-, polymer Data not available with N,N'-bis(2-aminoethyl)-1,2-ethanediamine

and (chloromethyl) oxirane

## Acute inhalation toxicity

Vapour concentrations above the recommended exposure levels may be irritating to the eyes and the respiratory tract, may cause headaches and dizziness, could be anesthetic and may have other central nervous system effects.

Substances Inhalation Vapor LC50 (Rat), mg/L/4hr

Crystalline Silica Data not available

#### Substances

## Inhalation Vapor LC50 (Rat), mg/L/4hr

Phenol, 4.4'-(1-methylethylidene) bis-, polymer Data not available with N,N'-bis(2-aminoethyl)-1,2-ethanediamine and (chloromethyl) oxirane

## Skin corrosion or irritation

Causes skin irritation. Frequent or prolonged contact may dry the skin, leading to discomfort and dermatitis.

## Serious eye damage or irritation

May be an eye irritant

## Respiratory or skin sensitisation

Vapour concentrations above the recommended exposure levels may be irritating to the eyes and the respiratory tract

## Germ cell mutagenicity

No information available on the product

# Carcinogenicity

Titanium Dioxide

The International Agency for Research on Cancer (IARC) has classified Titanium Dioxide as possibly carcinogenic to humans (Group 2B) based on inadequate evidence of carcinogenicity in humans and sufficient evidence of carcinogenicity in experimental animals

Crystalline Silica

The International Agency for Research on Cancer (IARC) has classified inhaled crystalline silica (CAS No. 14808-60-7) as a Group 1 carcinogen based on sufficient evident of carcinogenicity in humans and experimental animals. Exposure to inhaled crystalline silica can only occur when it is present in respirable form. Normal application procedures pose no hazard since the crystalline silica is wet and encapsulated, but grinding or sanding dried films of this product may yield respirable silica dusts.

# Reproductive toxicity

No information available on the product

## Specific Target Organ Toxicity (STOT)-single exposure

No information available on the product

## Specific Target Organ Toxicity (STOT)-repeated exposure

No information available on the product

# **Asphyxiation hazard**

May be harmful if swallowed and enters airways

# 12. ECOLOGICAL INFORMATION

## **Toxicity**

Aquatic toxicity -No data available

## Persistence and degradability

Biodegradation -No data available

## Bioaccumulative potential

No data available

# Mobility in soil

No data available

# Result of PBT and vPvB assessment

No data available

#### Other adverse effects

There is no ecotoxicological test data available on the product itself.

The product should not be allowed to enter drains or water courses.

## 13. DISPOSAL CONSIDERATIONS

The product should not be allowed to enter drains and watercourses.

Preferred methods of waste disposal are incineration or biological treatment in federal/state approved facility. Empty containers should be recycled or disposed through an approved waste management facility or licensed contractor.

All federal, state and local environmental regulations shall be observed.

# 14. TRANSPORT INFORMATION

Transport to be in accordance with ADR/RID for road/rail, IMDG for sea and IATA for Air.

#### LAND TRANSPORT

Not classified as Dangerous Goods by the criteria of the European Agreement concerning the international carriage of Dangerous Goods (ADR) by Road & Regulations concerning the international carriage of Dangerous goods (RID) by Rail.

UN Number: Not classified

Proper shipping name: - Class: -

Subsidary Risk(s): -

Packaging Group: Not assigned

## SEA TRANSPORT

Not classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport of Sea.

UN Number: Not classified

Proper shipping name: Class: Subsidary Risk(s): -

Packaging Group: Not assigned

Marine Pollutant No

# SEA (ANNEX II OF MARPOL 73/78 AND THE IBC CODE)

Not applicable

# **AIR TRANSPORT**

Not classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for transport by Air.

UN Number: Not classified

Proper shipping name: - Class: -

Subsidary Risk(s):

Packaging Group: Not assigned

## 15. REGULATORY INFORMATION

Applicable national regulations:

- Standards on Hazard communication for hazardous chemicals and dangerous goods
  - SS 586: Part 1: 2021-Transport and storage of dangerous goods
  - SS 586: Part 2: 2014-GHS of classification and labelling of chemicals
  - SS 586: Part 3: 2008(2014)-Preparation of safety data sheet
- MOM: Workplace Safety and Health Act & Workplace Safety and Health (General Provisions)
   Regulations
  - This product is subject to SDS, labelling, PEL and other requirements in the Acts/Regulations.
- NEA: Environmental Protection and Management Act & Environmental Protection and Management (Hazardous Substances) Regulations
  - This product is not subject to control under this Acts/Regulations.
- SCDF: Fire Safety Act & Fire Safety (Petroleum and Flammable Materials) Regulations
  - This product is not subject to the requirement of this Acts/Regulations.
- SPF: The Arms and Explosive Act, the Arms and Explosives (Explosives) Rules, and the Arms and Explosives (Explosive Precursors) Rules
  - This product is not subject to the requirement of this Acts/Regulations.

## 16. OTHER INFORMATION

Revision Date/Version No.: 19-08-2024 /3/1.1.1

History

Previous Revision Date / Version No.: not applicable //

#### Abbreviation:

ACGIH American Conference of Governmental Industrial Hygienists

TLV Threshold limit value

TWA Time-Weighted Average

OSHA Occupational Safety and Health Administration

PEL Permissible Exposure Limit

LD50 Lethal Dose

LC50 Median lethal concentration

IARC International Agency for Research in Cancer

## Disclaimer

To the best of our knowledge, the information contained herein is accurate. However, the information is provided without any representation or warranty, expressed or implied, regarding its accuracy or completeness. Since the conditions of handling, storage, use and disposal are beyond our control and may be beyond our knowledge, for this and other reasons, we make no guarantee of results and assume no liability for damages incurred by the use of this product. Please be reminded that all chemicals may present unknown health hazards and should be used with caution.