

**TECHNICAL DATA SHEET FOR**  
**ANTI-FUNGUS SOLUTION**

|                    |   |   |
|--------------------|---|---|
| <b>DESCRIPTION</b> | : | Anti-fungus Solution is used for surface preparation prior to painting to get rid of fungus growth and to kill any remaining fungus spores left on the substrate, so as to prevent the spore from germination |
| <b>TYPE</b>        | : | Water-based fungicidal wash   |
| <b>COLOUR</b>      | : | Colourless  |
| <b>FINISH</b>      | : | Not applicable  |
| <b>USES</b>        | : | Anti-fungus Solution is used in surface wash for masonry, brick, wood and plastering surfaces prior to painting   |
| <b>FEATURES</b>    | : | <ul style="list-style-type: none"><li>• Fast killing action</li><li>• Covers a wide spectrum of fungus and algae</li><li>• Easy application</li><li>• Formaldehyde-free</li></ul>                             |

**APPLICATION DATA**

|                                    |   |  |
|------------------------------------|---|--|
| <b>METHOD</b>                      | : | Brush, roller or air spray   |
| <b>THEORETICAL COVERAGE</b>        | : | 4 – 8 m <sup>2</sup> / litre (depend on substrate porosity)  |
| <b>DILUTION</b>                    | : | Not required   |
| <b>SURFACE PREPARATION</b>         | : | <ul style="list-style-type: none"><li>• Wash surface with water and remove unstable matter or organism as much as possible either by brushing, scrubbing or high jet pressure jet washing</li><li>• Apply Anti-Fungus Solution and leave on for at least 12 hours</li><li>• Ensure surface is dry and stable before painting with appropriate painting system.</li></ul> |
| <b>DRYING TIME</b>                 | : | Not applicable   |
| <b>OVERCOATING TIME</b>            | : | Not applicable   |
| <b>RECOMMENDED PAINTING SYSTEM</b> | : | Not applicable   |
| <b>CLEANING</b>                    | : | All equipments should be cleaned with water immediately after use  |

TECHNICAL DATA SHEET FOR

## ANTI-FUNGUS SOLUTION

### GENERAL INFORMATION

|                         |   |
|-------------------------|---|
| <b>SOLID CONTENT</b>    | : Not applicable  |
| <b>SPECIFIC GRAVITY</b> | : $0.98 \pm 3.0$ % kg / litre   |
| <b>PACKING</b>          | : 5 litres and 20 litres  |
| <b>STORAGE</b>          | : Store in a tightly sealed container in a cool, dry place  |
| <b>SHELF LIFE</b>       | : Up to 12 months in a tightly sealed container   |
| <b>PRECAUTION</b>       | : Ensure good ventilation during application and drying of paint. Avoid direct contact with sensitive skin. Use appropriate personal protective equipment |

Refer to the product Safety Data Sheet for more information

The information given is intended to give a description of the product performance under specific test conditions. Nevertheless, we cannot assume any responsibility for the use of it since circumstances under which the products are applied in practice are subjected to many variations. We reserve the right to alter the given data without notice.

|                                    |   |  |
|------------------------------------|---|--|
| <b>Enquiries / Contact Details</b> | : | <b>Customer Service</b><br><b>6265 5355 (Main Line)</b><br><b><a href="http://www.nipponpaint.com.sg">www.nipponpaint.com.sg</a></b> |
|------------------------------------|---|--|