



SAFETY DATA SHEET

SDS Number: SDS/OTH-0214

Version No: 003

1. IDENTIFICATION OF THE SUBSTANCE / MIXTURE AND OF THE COMPANY / UNDERTAKING

Product Name: DUFLON 4F II FRESH
Intended Use: Solvent-Based Protective Coating
Supplier/Manufacturer: Nippon Paint (S) Co. Pte Ltd
No. 1 First Lok Yang Road
Jurong Singapore 629728
Emergency Phone Number: (65) 6 265 5355
Fax Number: (65) 6 264 1603

2. HAZARDS IDENTIFICATION

GHS Classification:

Physical Hazard

Flammable Hazard Category 3

Health Hazard

Skin corrosion/Irritation Category 2

Serious eye damage/irritation Category 2

Specific target organ toxicity
-Single exposure Category 3

Environment Hazard

Not classified as an environmental hazard under GHS criteria

GHS Pictogram



Signal Word

Warning

Hazard statements

H226: Flammable liquid and vapour
H315: Causes skin irritation
H319: Causes serious eye irritation
H335: May cause respiratory irritation
H336: May cause drowsiness or dizziness

Precautionary statements

P210: Keep away from heat/sparks/open flames/hot surfaces – No smoking
P233: Keep container tightly closed
P240: Ground/bond container and receiving equipment
P241: Use explosion-proof electrical/ventilating/light/equipment
P242: Use only non-sparking tools
P243: Take precautionary measures against static discharge
P261: Avoid breathing dust/fume/gas/mist/vapours/spray
P264: Wash hands thoroughly after handling
P271: Use only outdoors or in a well-ventilated area

P280: Wear protective gloves/protective clothing/eye protection/face protection

Response

P312: Call a POISON CENTER or doctor/physician if you feel unwell

P321: Specific treatment (see Section 4 of SDS)

P362: Take off contaminated clothing and wash before reuse

P302+352: IF ON SKIN: Wash with soap and water

P303+361+353: IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower

P304+340: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

P332+313: If skin irritation occurs: Get medical advice/attention

P337+313: If eye irritation persists: Get medical advice/attention

P370+378: In case of fire: Use appropriate media for extinction

P303+361+353: IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower

P305+351+338: IF IN EYES: Rinse continuously with water for several minutes. Remove contact lenses if present and easy to do – continue rinsing

Storage

P405: Store locked up

P403+233: Store in a well ventilated place. Keep container tightly closed

P403+235: Store in a well ventilated place. Keep cool

Disposal

P501 Dispose of contents/container to appropriate waste site or reclaimer in accordance with local or national regulations

3. COMPOSITION / INFORMATION ON INGREDIENTS

<u>Ingredient</u>	<u>CAS No.</u>	<u>%</u>
n-Butyl acetate	123-86-4	9-20
Xylene	1330-20-7	3-6
Amphorous silica	7631-86-9	2-4
Zirconium oxide	1314-23-4	2-4
Heptan-2-one	110-43-0	1-3
Substances determined to be non-hazardous	-	Balance

4. FIRST-AID MEASURES

INHALATION

- Move person to fresh air and call for medical assistance immediately.
- If not breathing, give artificial respiration, if breathing is difficult, give oxygen. Keep at rest.

SKIN CONTACT

- In case of contact, immediately flush skin with large amounts of water and soap while removing contaminated clothing and shoes.
- If irritation persists, get medical attention.

EYE CONTACT

- Immediately flush eyes with large amounts of water until irritation subsides.
- Remove contact lens
- Obtain medical attention, preferably by an ophthalmologist, immediately.

INGESTION

- DO NOT induce vomiting unless directed to do so by a medical personnel. Never give anything by mouth to an unconscious person. Keep at rest. Get medical attention immediately.

5. FIRE FIGHTING MEASURES

SUITABLE FIRE EXTINGUISHING MEDIA

- Alcohol-resistant foam, Carbon dioxide, or dry chemical type

SPECIFIC HAZARDS ARISING FROM THE CHEMICAL

- Combustion products may include and are not limited to: Carbon monoxide and Carbon dioxide.

SPECIAL PROTECTIVE ACTIONS FOR FIRE FIGHTERS

- Wear full protective clothing and NIOSH-approved self-contained breathing apparatus.
- Use water spray to cool fire-exposed surfaces and to protect personnel. If a leak or spill has not ignited, use water spray to disperse the vapours.
- If possible, isolate product from heat, electrical equipments, sparks and open flames.
- Avoid spraying water directly into storage containers.
- Closed containers may explode when exposed to extreme heat.
- Avoid spreading burning liquid with water, isolate liquid.
- Do not allow run-off from fire fighting to enter drains or watercourses.

6. ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT AND EMERGENCY PROCEDURE

- Wear appropriate protective equipment, e.g. respirators, eye protection, gloves and safety shoes.
- Avoid substance contact with eyes. Do not inhale vapours.
- Ensure supply of fresh air in enclosed rooms.

ENVIRONMENTAL PRECAUTIONS

- Eliminate sources of ignition.
- Keep public away.
- Contain spilled liquid with sand or other non-combustible absorbent materials
- Wash area and prevent runoff into drains and sewerage system.
- Advise authorities if substance has entered a watercourse or sewer or has contaminated soil or vegetation.

METHODS AND MATERIALS FOR CONTAINMENTS AND CLEANING UP

- Clean up all spills immediately.
- Absorb spill with absorbent and inert material, then place in container.
- Disposal in accordance to local/national regulations.

7. HANDLING AND STORAGE

PRECAUTIONS FOR SAFE HANDLING

- Use appropriate personal protective equipment
- Keep out of reach of children.
- Handle containers with care. Open slowly in order to control possible pressure release.
- Do not pressurize containers.
- Do not ingest. Do not breathe in gas/fumes/vapour. Avoid contact with skin and eyes.
- For personal protection, see section 8.
- Use only in areas from which all naked lights and other sources of ignition have been excluded.
- Take precautionary measures against static discharge
- Protect from frost and extremes of temperature.

CONDITIONS FOR SAFE STORAGE, INCLUDING ANY INCOMPATIBILITIES

- Keep containers tightly closed.
- Containers that are opened should be properly resealed and kept upright to prevent leakage.

- Store in cool, dry and well-ventilated place at temperature between 20°C to 40°C away from heat and sources of ignition.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

CONTROL PARAMETERS/OCCUPATIONAL LIMITS

Substances	ACGIH TLV-TWA		OSHA PEL-TWA	
	ppm	mg/m³	ppm	mg/m³
n-Butyl acetate	-	-	-	15
Xylene	100	434	-	-
Amphorous silica	-	-	-	-
Zirconium oxide	-	-	-	-
Heptan-2-one	50	-	100	465

APPROPRIATE ENGINEERING CONTROL MEASURES

- Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapours below their respective occupational exposure limits.
- Ensure eyewash stations and safety showers are close to the workstation location.

PERSONAL PROTECTION

Respiratory Protection:	Use of NIOSH-approved respirators with organic vapour cartridges is recommended.
Hand Protection:	Use of solvent resistance type or chemical resistant type of protective gloves is recommended.
Eye Protection:	Use of safety glasses or goggles with side shields is recommended.
Skin / Body Protection:	Wear chemical resistant clothes and safety shoes when handling product.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	: Liquid
Odour	: Aromatic hydrocarbon odour
Odour threshold	: Not available
pH	: Not available
Melting point/freezing point	: Not available
Initial boiling point and boiling range	: Between 124 and 202 °C
Flash point	: 23 °C
Evaporation rate	: Not available
Flammability (solid, gas)	: Not applicable
Lower flammability or explosive limit	: 1% by vol
Upper flammability or explosive limit	: 13.1% by vol
Vapour pressure	: Not available
Vapour density	: > 1.00 (Vapour is heavier than air)
Relative density	: Not available
Solubility	: Not Miscible in water
Partition coefficient	: Not available
Auto-ignition temperature	: > 315 °C
Decomposition temperature	: Not available
Viscosity	: 82 - 92 KU

10. STABILITY AND REACTIVITY

REACTIVITY

- No dangerous reaction known under condition of normal use.

CHEMICAL STABILITY

- The product is stable under recommended storage and handling conditions. (see section 7)

POSSIBILITY OF HAZARDOUS REACTION

- Under normal conditions of storage and use, hazardous reaction will not occur.

CONDITIONS TO AVOID

- Keep away from oxidising agents, strongly alkaline and strongly acidic materials in order to avoid exothermic reactions. Avoid all possible sources of ignition (spark or flame). Do not pressurize, cut, weld, braze, drill, grind or expose containers to heat or sources of ignition.

HAZARDOUS DECOMPOSITION PRODUCTS

- When exposed to high temperatures may produce hazardous decomposition products such as carbon monoxide, carbon dioxide, oxides of nitrogen and smoke.

11. TOXICOLOGICAL INFORMATION

There is no data available on the product itself.

Toxicological information of ingredients:

Acute Oral toxicity

Harmful if swallowed

<u>Substances</u>	<u>Oral LD50(Rat), mg/kg</u>
n-butyl acetate	10700
Xylene	4300
Amphorous silica	3160
Zirconium oxide	Data not available
Heptan-2-one	1600

Acute dermal/skin toxicity

May be harmful if in contact with skin

<u>Substances</u>	<u>Dermal LD50 (Rabbit), mg/kg</u>
n-butyl acetate	3160
Zirconium oxide	Data not available
Heptan-2-one	1600

Acute inhalation toxicity

Vapour concentrations above the recommended exposure levels may be irritating to the eyes and the respiratory tract, may cause headaches and dizziness, could be anesthetic and may have other central nervous system effects

<u>Substances</u>	<u>Inhalation Vapor LC50 (Rat), mg/L/4hr</u>
n-butyl acetate	Data not available
Xylene	5000
Amphorous silica	Data not available
Zirconium oxide	Data not available
Heptan-2-one	16.7

Skin corrosion or irritation

Causes skin irritation. Frequent or prolonged contact may dry the skin, leading to discomfort and dermatitis.

Serious eye damage or irritation

May be an eye irritant.

Respiratory or skin sensitisation

Vapour concentrations above the recommended exposure levels may be irritating to the eyes and the respiratory tract.

Germ cell mutagenicity

No information available on the product.

Carcinogenicity

Titanium Dioxide

The International Agency for Research on Cancer (IARC) has classified Titanium Dioxide as possibly carcinogenic to humans (Group 2B) based on inadequate evidence of carcinogenicity in humans and sufficient evidence of carcinogenicity in experimental animals

Reproductive toxicity

No information available on the product.

Specific Target Organ Toxicity (STOT)- single exposure

No information available on the product.

Specific Target Organ Toxicity (STOT)- repeated exposure

No information available on the product.

Aspiration hazard

No information available on the product.

12. ECOLOGICAL INFORMATION

Toxicity

-No data available

Persistence and degradability

Biodegradation -No data available

Bioaccumulative potential

-No data available

Mobility in soil

-No data available

Result of PBT and vPvB assessment

-No data available

Other adverse effects

There is no ecotoxicological test data available on the product itself.
The product should not be allowed to enter drains or water courses

13. DISPOSAL CONSIDERATIONS

The product should not be allowed to enter drains and watercourses.
Preferred methods of waste disposal are incineration or biological treatment in federal/state approved facility. Empty containers should be recycled or disposed through an approved waste management facility or licensed contractor.

All federal, state and local environmental regulations shall be observed.

14. TRANSPORT INFORMATION

Transport to be in accordance with ADR/RID for road/rail, IMDG for sea and IATA for Air.

LAND TRANSPORT

Classified as Dangerous Goods by the criteria of the European Agreement concerning the international carriage of Dangerous Goods (ADR) by Road & Regulations concerning the international carriage of Dangerous goods (RID) by Rail.

UN Number: 1263
 Proper shipping name: PAINT (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base) or PAINT RELATED MATERIAL (including paint thinning or reducing compound)
 Class: 3
 Subsidiary Risk(s): -
 Packaging Group: III

SEA TRANSPORT

Classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport of Sea.

UN Number: 1263
 Proper shipping name: PAINT (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base) or PAINT RELATED MATERIAL (including paint thinning or reducing compound)
 Class: 3
 Subsidiary Risk(s): -
 Packaging Group: III
 Marine Pollutant No

SEA (Annex II of MARPOL 73/78 and the IBC code)

Not applicable

AIR TRANSPORT

Dangerous Goods Regulations for transport by Air

UN Number: 1263
 Proper shipping name: PAINT (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base) or PAINT RELATED MATERIAL (including paint thinning or reducing compound)
 Class: 3
 Subsidiary Risk(s): -
 Packaging Group: III

15. REGULATORY INFORMATION

Applicable national regulations:

- Standards on Hazard communication for hazardous chemicals and dangerous goods
 - SS 586 : Part 1: 2014- Transport and storage of dangerous goods
 - SS 586 : Part 2: 2014- GHS of classification and labelling of chemicals- Singapore's adaptations
 - SS 586 : Part 3: 2008- Preparation of safety data sheets (SDS)
- MOM: Workplace Safety and Health Act & Workplace Safety and Health (General Provisions) Regulations
 - This product is subject to SDS, labelling, PEL and other requirements in the Acts/Regulations
- NEA: Environmental Protection and Management Act & Environmental Protection and Management (Hazardous Substances) Regulations.
 - This product is not subject to control under this Acts/Regulations
- SCDF: Fire Safety Act & Fire Safety (Petroleum and Flammable Materials) Regulations
 - This product is subject to the requirement of this Acts/Regulations
- SPF: The Arms and Explosive Act, the Arms and Explosives (Explosives) Rules, and the Arms and Explosives (Explosive Precursors) Rules
 - This product is not subject to the requirement of this Acts/Regulations

16. OTHER INFORMATION

Revision date: 3-Jan-2020

Abbreviation

ACGIH American Conference of Governmental Industrial Hygienists

TLV Threshold limit value

TWA Time-Weighted Average

OSHA Occupational Safety and Health Administration

PEL Permissible Exposure Limit

LD50 Lethal Dose

LC50 Median lethal concentration

IACR International Agency for Research in Cancer

Disclaimer

To the best of our knowledge, the information contained herein is accurate. However, the information is provided without any representation or warranty, expressed or implied, regarding its accuracy or completeness. Since the conditions of handling, storage, use and disposal are beyond our control and may be beyond our knowledge, for this and other reasons, we make no guarantee of results and assume no liability for damages incurred by the use of this product. Please be reminded that all chemicals may present unknown health hazards and should be used with caution.



SAFETY DATA SHEET

SDS Number: SDS/OTH-0215

Version No: 003

1. IDENTIFICATION OF THE SUBSTANCE / MIXTURE AND OF THE COMPANY / UNDERTAKING

Product Name: **DUFLON 4F II FRESH HARDENER**
Intended Use: Solvent-Based Protective Coating
Supplier/Manufacturer: Nippon Paint (S) Co. Pte Ltd
No. 1 First Lok Yang Road
Jurong Singapore 629728
Emergency Phone Number: (65) 6 265 5355
Fax Number: (65) 6 264 1603

2. HAZARDS IDENTIFICATION

GHS Classification:

Physical Hazard

Flammable Hazard Category 3

Health Hazard

Acute Toxicity:
- Inhalation Category 1
Skin corrosion/Irritation Category 1
Serious eye damage/irritation Category 1
Respiratory sensitization Category 1
Skin sensitization Category 1
Specific target organ toxicity
-Single exposure Category 3

Environment Hazard

Not classified as an environmental hazard under GHS criteria

GHS Pictogram



Signal Word

Danger

Hazard statements

H226: Flammable liquid and vapour
H314: Causes severe skin burns and eye damage
H317: May cause an allergic skin reaction
H318: Causes serious eye irritation
H330: Fatal if inhaled
H334: May cause allergy or asthma symptoms or breathing difficulties if inhaled
H335: May cause respiratory irritation
H336: May cause drowsiness or dizziness

Precautionary statements

P210: Keep away from heat/sparks/open flames/hot surfaces – No smoking
P233: Keep container tightly closed

- P240: Ground/bond container and receiving equipment
- P241: Use explosion-proof electrical/ventilating/light/equipment
- P242: Use only non-sparking tools
- P243: Take precautionary measures against static discharge
- P260: Do not breathe dust/fume/gas/mist/vapours/spray
- P261: Avoid breathing dust/fume/gas/mist/vapours/spray
- P264: Wash hands thoroughly after handling
- P271: Use only outdoors or in a well-ventilated area
- P273: Avoid release to the environment
- P280: Wear protective gloves/protective clothing/eye protection/face protection
- P284: Wear respiratory protection
- P285: In case of inadequate ventilation wear respiratory protection

Response

- P310: Immediately call a POISON CENTER or doctor/physician
- P312: Call a POISON CENTER or doctor/physician if you feel unwell
- P320: Specific treatment is urgent (see . . .on this label)
- P321: Specific treatment (see Section 4 of SDS)
- P363: Wash contaminated clothing before reuse
- P302+352: IF ON SKIN: Wash with soap and water
- P304+340: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing
- P304+341: IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable Remove victim to fresh air and keep at rest in a position comfortable for breathing
- P333+313: If skin irritation or a rash occurs: Get medical advice/attention
- P342+311: Call a POISON CENTER or doctor/physician
- P337+313: If eye irritation persists: Get medical advice/attention
- P370+378: In case of fire: Use appropriate media for extinction
- P301+330+331: IF SWALLOWED: Rinse mouth. Do NOT induce vomiting
- P303+361+353: IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower
- P305+351+338: IF IN EYES: Rinse continuously with water for several minutes. Remove contact lenses if present and easy to do – continue rinsing

Storage

- P405: Store locked up
- P403+233: Store in a well ventilated place. Keep container tightly closed
- P403+235: Store in a well ventilated place. Keep cool

Disposal

P501 Dispose of contents/container to appropriate waste site or reclaimer in accordance with local or national regulations

3. COMPOSITION / INFORMATION ON INGREDIENTS

Ingredient	CAS No.	%
n-butyl acetate	123-86-4	13-28
3-(trimethoxysilyl)propylisocyanate	15396-00-6	3-7
Substances determined to be non-hazardous	-	Balance

4. FIRST-AID MEASURES

INHALATION

- Move person to fresh air and call for medical assistance immediately.
- If not breathing, give artificial respiration, if breathing is difficult, give oxygen. Keep at rest.

SKIN CONTACT

- In case of contact, immediately flush skin with large amounts of water and soap while removing contaminated clothing and shoes.
- If irritation persists, get medical attention.

EYE CONTACT

- Immediately flush eyes with large amounts of water until irritation subsides.
- Remove contact lens
- Obtain medical attention, preferably by an ophthalmologist, immediately.

INGESTION

- DO NOT induce vomiting unless directed to do so by a medical personnel. Never give anything by mouth to an unconscious person. Keep at rest. Get medical attention immediately.

5. FIRE FIGHTING MEASURES

SUITABLE FIRE EXTINGUISHING MEDIA

- Alcohol-resistant foam, Carbon dioxide, or dry chemical type

SPECIFIC HAZARDS ARISING FROM THE CHEMICAL

- Combustion products may include and are not limited to: Carbon monoxide and Carbon dioxide.

SPECIAL PROTECTIVE ACTIONS FOR FIRE FIGHTERS

- Wear full protective clothing and NIOSH-approved self-contained breathing apparatus.
- Use water spray to cool fire-exposed surfaces and to protect personnel. If a leak or spill has not ignited, use water spray to disperse the vapours.
- If possible, isolate product from heat, electrical equipments, sparks and open flames.
- Avoid spraying water directly into storage containers.
- Closed containers may explode when exposed to extreme heat.
- Avoid spreading burning liquid with water, isolate liquid.
- Do not allow run-off from fire fighting to enter drains or watercourses.

6. ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT AND EMERGENCY PROCEDURE

- Wear appropriate protective equipment, e.g. respirators, eye protection, gloves and safety shoes.
- Avoid substance contact with eyes. Do not inhale vapours.
- Ensure supply of fresh air in enclosed rooms.

ENVIRONMENTAL PRECAUTIONS

- Eliminate sources of ignition.
- Keep public away.
- Contain spilled liquid with sand or other non-combustible absorbent materials
- Wash area and prevent runoff into drains and sewerage system.
- Advise authorities if substance has entered a watercourse or sewer or has contaminated soil or vegetation.

METHODS AND MATERIALS FOR CONTAINMENTS AND CLEANING UP

- Clean up all spills immediately.
- Absorb spill with absorbent and inert material, then place in container.
- Disposal in accordance to local/national regulations.

7. HANDLING AND STORAGE

PRECAUTIONS FOR SAFE HANDLING

- Use appropriate personal protective equipment
- Keep out of reach of children.

- Handle containers with care. Open slowly in order to control possible pressure release.
- Do not pressurize containers.
- Do not ingest. Do not breathe in gas/fumes/vapour. Avoid contact with skin and eyes.
- For personal protection, see section 8.
- Use only in areas from which all naked lights and other sources of ignition have been excluded.
- Take precautionary measures against static discharge
- Protect from frost and extremes of temperature.

CONDITIONS FOR SAFE STORAGE, INCLUDING ANY INCOMPATIBILITIES

- Keep containers tightly closed.
- Containers that are opened should be properly resealed and kept upright to prevent leakage.
- Store in cool, dry and well-ventilated place at temperature between 20°C to 40°C away from heat and sources of ignition.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

CONTROL PARAMETERS/OCCUPATIONAL LIMITS

<u>Substances</u>	<u>ACGIH TLV-TWA</u>		<u>OSHA PEL-TWA</u>	
	<u>ppm</u>	<u>mg/m3</u>	<u>ppm</u>	<u>mg/m3</u>
n-Butyl acetate	-	-	-	-
3-(trimethoxysilyl)propylisocyanate	-	-	-	-

APPROPRIATE ENGINEERING CONTROL MEASURES

- Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapours below their respective occupational exposure limits.
- Ensure eyewash stations and safety showers are close to the workstation location.

PERSONAL PROTECTION

Respiratory Protection: Use of NIOSH-approved respirators with organic vapour cartridges is recommended.

Hand Protection: Use of solvent resistance type or chemical resistant type of protective gloves is recommended.

Eye Protection: Use of safety glasses or goggles with side shields is recommended.

Skin / Body Protection: Wear chemical resistant clothes and safety shoes when handling product.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : Liquid

Odour : Aromatic hydrocarbon

Odour threshold : Not available

pH : Not available

Melting point/freezing point : Not available

Initial boiling point and boiling range : Between 124 and 233 °C

Flash point : 24 °C

Evaporation rate : Not available

Flammability (solid, gas) : Not applicable

Lower flammability or explosive limit : 1.7% by vol

Upper flammability or explosive limit : 7.6% by vol

Vapour pressure : Not available

Vapour density : > 1.00 (Vapour is heavier than air)

Relative density : Not available

Solubility : Not Miscible in water

Partition coefficient : Not available

Auto-ignition temperature : Not available

Decomposition temperature	:	Not available
Viscosity	:	12 - 16 sec (Ford Cup)

10. STABILITY AND REACTIVITY

REACTIVITY

- No dangerous reaction known under condition of normal use.

CHEMICAL STABILITY

- The product is stable under recommended storage and handling conditions. (see section 7)

POSSIBILITY OF HAZARDOUS REACTION

- Under normal conditions of storage and use, hazardous reaction will not occur.

CONDITIONS TO AVOID

- Keep away from oxidising agents, strongly alkaline and strongly acidic materials in order to avoid exothermic reactions. Avoid all possible sources of ignition (spark or flame). Do not pressurize, cut, weld, braze, drill, grind or expose containers to heat or sources of ignition.

HAZARDOUS DECOMPOSITION PRODUCTS

- When exposed to high temperatures may produce hazardous decomposition products such as carbon monoxide, carbon dioxide, oxides of nitrogen and smoke.

11. TOXICOLOGICAL INFORMATION

There is no data available on the product itself.

Toxicological information of ingredients:

Acute Oral toxicity

Harmful if swallowed

<u>Ingredient</u>	<u>Oral LD50(Rat), mg/kg</u>
n-butyl acetate	10700
3-(trimethoxysilyl)propylisocyanate	878

Acute dermal/skin toxicity

May be harmful if in contact with skin

<u>Ingredient</u>	<u>Dermal LD50 (Rabbit), mg/kg</u>
n-butyl acetate	17600
3-(trimethoxysilyl)propylisocyanate	1190

Acute inhalation toxicity

Vapour concentrations above the recommended exposure levels may be irritating to the eyes and the respiratory tract, may cause headaches and dizziness, could be anesthetic and may have other central nervous system effects.

<u>Ingredient</u>	<u>Inhalation Vapor LC50 (Rat), mg/L/4hr</u>
n-butyl acetate	Data not available
3-(trimethoxysilyl)propylisocyanate	Data not available

Skin corrosion or irritation

Causes skin irritation. Frequent or prolonged contact may dry the skin, leading to discomfort and dermatitis.

Serious eye damage or irritation

May be an eye irritant.

Respiratory or skin sensitisation

Vapour concentrations above the recommended exposure levels may be irritating to the eyes and the respiratory tract.

Germ cell mutagenicity

No information available on the product.

Carcinogenicity

No information available on the product.

Reproductive toxicity

No information available on the product.

Specific Target Organ Toxicity (STOT)- single exposure

No information available on the product.

Specific Target Organ Toxicity (STOT)- repeated exposure

No information available on the product.

Aspiration hazard

May be harmful if swallowed and enters airways

12. ECOLOGICAL INFORMATION

Toxicity

Aquatic toxicity -No data available

Persistence and degradability

Biodegradation -No data available

Bioaccumulative potential

-No data available

Mobility in soil

-No data available

Result of PBT and vPvB assessment

-No data available

Other adverse effects

There is no ecotoxicological test data available on the product itself.
The product should not be allowed to enter drains or water courses

13. DISPOSAL CONSIDERATIONS

The product should not be allowed to enter drains and watercourses.
Preferred methods of waste disposal are incineration or biological treatment in federal/state approved facility. Empty containers should be recycled or disposed through an approved waste management facility or licensed contractor.

All federal, state and local environmental regulations shall be observed.

14. TRANSPORT INFORMATION

Transport to be in accordance with ADR/RID for road/rail, IMDG for sea and IATA for Air.

LAND TRANSPORT

Classified as Dangerous Goods by the criteria of the European Agreement concerning the international carriage of Dangerous Goods (ADR) by Road & Regulations concerning the

international carriage of Dangerous goods (RID) by Rail.

UN Number: 1263

Proper shipping name: PAINT (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base) or PAINT RELATED MATERIAL (including paint thinning or reducing compound)

Class: Class 3

Packaging Group: III

SEA TRANSPORT

Classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport of Sea.

UN Number: 1263

Proper shipping name: PAINT (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base) or PAINT RELATED MATERIAL (including paint thinning or reducing compound)

Class: Class 3

Packaging Group: III

Marine Pollutant No

SEA (Annex II of MARPOL 73/78 and the IBC code)

Not applicable

AIR TRANSPORT

Classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for transport by Air

UN Number: 1263

Proper shipping name: PAINT (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base) or PAINT RELATED MATERIAL (including paint thinning or reducing compound)

Class: Class 3

Packaging Group: III

15. REGULATORY INFORMATION

Applicable national regulations:

- Standards on Hazard communication for hazardous chemicals and dangerous goods
 - SS 586 : Part 1: 2014- Transport and storage of dangerous goods
 - SS 586 : Part 2: 2014- GHS of classification and labelling of chemicals- Singapore's adaptations
 - SS 586 : Part 3: 2008- Preparation of safety data sheets (SDS)
- MOM: Workplace Safety and Health Act & Workplace Safety and Health (General Provisions) Regulations
 - This product is subject to SDS, labelling, PEL and other requirements in the Acts/Regulations
- NEA: Environmental Protection and Management Act & Environmental Protection and Management (Hazardous Substances) Regulations.
 - This product is not subject to control under this Acts/Regulations
- SCDF: Fire Safety Act & Fire Safety (Petroleum and Flammable Materials) Regulations
 - This product is subject to the requirement of this Acts/Regulations
- SPF: The Arms and Explosive Act, the Arms and Explosives (Explosives) Rules, and the Arms and Explosives (Explosive Precursors) Rules
 - This product is not subject to the requirement of this Acts/Regulations

16. OTHER INFORMATION

Revision date: 3-Jan-2020

Abbreviation

ACGIH American Conference of Governmental Industrial Hygienists
TLV Threshold limit value
TWA Time-Weighted Average
OSHA Occupational Safety and Health Administration
PEL Permissible Exposure Limit
LD50 Lethal Dose
LC50 Median lethal concentration
IACR International Agency for Research in Cancer

Disclaimer

To the best of our knowledge, the information contained herein is accurate. However, the information is provided without any representation or warranty, expressed or implied, regarding its accuracy or completeness. Since the conditions of handling, storage, use and disposal are beyond our control and may be beyond our knowledge, for this and other reasons, we make no guarantee of results and assume no liability for damages incurred by the use of this product. Please be reminded that all chemicals may present unknown health hazards and should be used with caution.