



# SAFETY DATA SHEET

SDS Number: SDS-70627

Version No: 003

Revision Date/Version No:08-02-2024 /3/2.3.3

---

## 1. IDENTIFICATION OF THE SUBSTANCE / MIXTURE AND OF THE COMPANY / UNDERTAKING

---

Product Name:	HI-ALKYD 1402 ZINC PHOSPHATE HB PRIMER GREY
Intended Use:	Solvent-Based Protective Coating
Manufacturer:	Nippon Paint (S) Co. Pte Ltd No. 1 First Lok Yang Road Jurong Singapore 629728
Emergency Phone Number:	(65) 6 265 5355
Fax Numbers:	(65) 6 264 1603

---

## 2. HAZARDS IDENTIFICATION

---

### GHS Classification:

#### Physical Hazard

Flammable Hazard Category 3

#### Health Hazard

Acute Toxicity:  
- Oral Category 4  
- Inhalation Category 1  
Skin corrosion/irritation Category 2  
Serious eye damage/irritation Category 2  
Germ cell mutagenicity Category 1  
Carcinogenicity Category 1

#### Environmental Hazard

Not classified as an environmental hazard under GHS criteria

#### GHS Pictogram



#### Signal Word

Danger

#### Hazard statements

H226: Flammable liquid and vapour

---

H302: Harmful if swallowed  
H315: Causes skin irritation  
H319: Causes serious eye irritation  
H330: Fatal if inhaled  
H340: May cause genetic defects  
H350: May cause cancer

#### Precautionary statements

P201: Obtain special instructions before use  
P202: Do not handle until all safety precautions have been read and understood  
P210: Keep away from heat/sparks/open flames/hot surfaces – No smoking  
P233: Keep container tightly closed  
P240: Ground/bond container and receiving equipment  
P241: Use explosion-proof electrical/ventilating/light/equipment  
P242: Use only non-sparking tools  
P243: Take precautionary measures against static discharge  
P260: Do not breathe dust/fume/gas/mist/vapours/spray  
P264: Wash hands thoroughly after handling  
P270: Do not eat, drink or smoke when using this product  
P271: Use only outdoors or in a well-ventilated area  
P280: Wear protective gloves/protective clothing/eye protection/face protection  
P281: Use personal protective equipment as required  
P284: Wear respiratory protection

#### Response

P310: Immediately call a POISON CENTER or doctor/physician  
P320: Specific treatment is urgent (see ... on this label)  
P321: Specific treatment (see Section 4 of SDS)  
P330: Rinse mouth  
P362: Take off contaminated clothing and wash before reuse  
P301+312: IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell  
P302+352: IF ON SKIN: Wash with soap and water  
P304+340: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing  
P308+313: IF exposed or concerned: Get medical advice/attention  
P332+313: If skin irritation occurs: Get medical advice/attention  
P337+313: If eye irritation persists: Get medical advice/attention  
P370+378: In case of fire: Use appropriate media for extinction  
P303+361+353: IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower  
P305+351+338: IF IN EYES: Rinse continuously with water for several minutes. Remove contact lenses if present and easy to do – continue rinsing

#### Storage

P405: Store locked up  
P403+233: Store in a well ventilated place. Keep container tightly closed  
P403+235: Store in a well ventilated place. Keep cool

#### Disposal

P501: Dispose of contents/container to appropriate waste site or reclaimer in accordance with local or national regulations

---

### **3. COMPOSITION / INFORMATION ON INGREDIENTS**

---

Substances	CAS No.	%
Xylene	1330-20-7	16-36
Linseed oil, polymer with formaldehyde, glycerol, pentaerythritol, phenol, phthalic anhydride and rosin	68131-08-8	9-20
Substances determined to be non-hazardous	-	Balance
		100%

---

## 4. FIRST-AID MEASURES

---

### INHALATION

- Move person to fresh air and call for medical assistance immediately.
- If not breathing, give artificial respiration, if breathing is difficult, give oxygen. Keep at rest.

### SKIN CONTACT

- In case of contact, immediately flush skin with large amounts of water and soap while removing contaminated clothing and shoes.
- If irritation persists, get medical attention.

### EYE CONTACT

- Immediately flush eyes with large amounts of water until irritation subsides.
- Remove contact lens.
- Obtain medical attention, preferably by an ophthalmologist, immediately.

### INGESTION

- DO NOT induce vomiting unless directed to do so by a medical personnel. Never give anything by mouth to an unconscious person. Keep at rest. Get medical attention immediately.

---

## 5. FIRE FIGHTING MEASURES

---

### SUITABLE FIRE EXTINGUISHING MEDIA

- Alcohol - resistant foam, Carbon dioxide, or dry chemical type.

### SPECIFIC HAZARDS ARISING FROM THE CHEMICAL

- Combustion products may include and are not limited to: Carbon monoxide and Carbon dioxide.

### SPECIAL PROTECTIVE ACTIONS FOR FIRE FIGHTERS

- Wear full protective clothing and NIOSH - approved self - contained breathing apparatus.
- Use water spray to cool fire - exposed surfaces and to protect personnel. If a leak or spill has not ignited, use water spray to disperse the vapours.
- If possible, isolate product from heat, electrical equipments, sparks and open flames.
- Avoid spraying water directly into storage containers.
- Closed containers may explode when exposed to extreme heat.
- Avoid spreading burning liquid with water, isolate liquid.
- Do not allow runoff from fire fighting to enter drains or watercourses.

---

## 6. ACCIDENTAL RELEASE MEASURES

---

### PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT AND EMERGENCY PROCEDURE

- Wear appropriate protective equipment, e.g. respirators, eye protection, gloves and safety shoes.
- Avoid substance contact with eyes. Do not inhale vapours.
- Ensure supply of fresh air in enclosed rooms.

**ENVIRONMENTAL PRECAUTIONS**

- Eliminate sources of ignition.
- Keep public away.
- Contain spilled liquid with sand or other non-combustible absorbent materials.
- Wash area and prevent runoff into drains and sewerage system.
- Advise authorities if substance has entered a watercourse or sewer or has contaminated soil or vegetation.

**METHODS AND MATERIALS FOR CONTAINMENTS AND CLEANING UP**

- Clean up all spills immediately.
- Absorb spill with absorbent and inert material, then place in container.
- Disposal in accordance to local/national regulations.

**7. HANDLING AND STORAGE**

**PRECAUTIONS FOR SAFE HANDLING**

- Use appropriate personal protective equipment
- Keep out of reach of children.
- Handle containers with care. Open slowly in order to control possible pressure release.
- Do not pressurize containers.
- Do not ingest. Do not breathe in gas/fumes/vapour. Avoid contact with skin and eyes.
- For personal protection, see section 8.
- Use only in areas from which all naked lights and other sources of ignition have been excluded.
- Take precautionary measures against static discharge
- Protect from frost and extremes of temperature

**CONDITIONS FOR SAFE STORAGE, INCLUDING ANY INCOMPATIBILITIES**

- Keep containers tightly closed
- Containers that are opened should be properly resealed and kept upright to prevent leakage.
- Store in cool, dry and well - ventilated place at temperature between 20°C to 40°C away from heat and sources of ignition

**8. EXPOSURE CONTROLS / PERSONAL PROTECTION**

**CONTROL PARAMETERS/OCCUPATIONAL LIMITS**

Substances	ACGIH TLV-TWA		OSHA PEL-TWA	
	ppm	mg/m <sup>3</sup>	ppm	mg/m <sup>3</sup>
Xylene	100	434.00	-	-
Linseed oil, polymer with formaldehyde, glycerol, pentaerythritol, phenol, phthalic anhydride and rosin	-	-	-	-

**APPROPRIATE ENGINEERING CONTROL MEASURES**

- Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapours below their respective occupational exposure limits.
- Ensure eyewash stations and safety showers are close to the workstation location.

**PERSONAL PROTECTION**

Respiratory Protection:	Use of NIOSH - approved respirators with organic vapour cartridges is recommended.
Hand Protection:	Use of solvent resistance type or chemical resistant type of protective gloves is recommended.
Eye Protection:	Use of safety glasses or goggles with side shields is recommended.
Skin / Body Protection:	Wear chemical resistant clothes and safety shoes when handling product.

**9. PHYSICAL AND CHEMICAL PROPERTIES**

Appearance	: Liquid
Odour	: Aromatic hydrocarbon odour
Odour threshold	: Not available
pH	: Not available
Melting point/freezing point	: Not available
Initial boiling point and boiling range	: Between 90 and 160 °C
Flash point	: 23 °C
Evaporation rate	: Not available
Flammability (solid, gas)	: Not applicable
Lower flammability or explosive limit	: 1.1 % by vol
Upper flammability or explosive limit	: 7 % by vol
Vapour pressure	: Not available
Vapour density	: > 1.00 (Vapour is heavier than air)
Relative density	: Not available
Solubility	: Not Miscible in water
Partition coefficient	: Not available
Auto-ignition temperature	: > 230 °C
Decomposition temperature	: Not available
Viscosity	: 64 - 68 KU

**10. STABILITY AND REACTIVITY**

**REACTIVITY**

- No dangerous reaction known under condition of normal use

**CHEMICAL STABILITY**

- The product is stable under recommended storage and handling conditions. (see section7)

**POSSIBILITY OF HAZARDOUS REACTION**

- Under normal conditions of storage and use, hazardous reaction will not occur

**CONDITIONS TO AVOID**

- Keep away from oxidising agents, strongly alkaline and strongly acidic materials in order to avoid exothermic reactions. Avoid all possible sources of ignition (spark or flame). Do not pressurize, cut, weld, braze, drill, grind or expose containers to heat or sources of ignition

**HAZARDOUS DECOMPOSITION PRODUCTS**

- When exposed to high temperatures may produce hazardous decomposition products such as carbon monoxide, carbon dioxide, oxides of nitrogen and smoke.

---

## 11. TOXICOLOGICAL INFORMATION

---

There is no data available on the product itself.  
 Toxicological information of substances:

### **Acute oral toxicity**

Harmful if swallowed

<u>Substances</u>	<u>Oral LD50(Rat), mg/kg</u>
Xylene	4300
Linseed oil, polymer with formaldehyde, glycerol, pentaerythritol, phenol, phthalic anhydride and rosin	Data not available

### **Acute dermal/skin toxicity**

May be harmful if in contact with skin

<u>Substances</u>	<u>Dermal LD50 (Rabbit), mg/kg</u>
Xylene	1700
Linseed oil, polymer with formaldehyde, glycerol, pentaerythritol, phenol, phthalic anhydride and rosin	Data not available

### **Acute inhalation toxicity**

Vapour concentrations above the recommended exposure levels may be irritating to the eyes and the respiratory tract, may cause headaches and dizziness, could be anesthetic and may have other central nervous system effects.

<u>Substances</u>	<u>Inhalation Vapor LC50 (Rat), mg/L/4hr</u>
Xylene	5000
Linseed oil, polymer with formaldehyde, glycerol, pentaerythritol, phenol, phthalic anhydride and rosin	Data not available

### **Skin corrosion or irritation**

Causes skin irritation. Frequent or prolonged contact may dry the skin, leading to discomfort and dermatitis.

### **Serious eye damage or irritation**

May be an eye irritant

### **Respiratory or skin sensitisation**

Vapour concentrations above the recommended exposure levels may be irritating to the eyes and the respiratory tract

### **Germ cell mutagenicity**

No information available on the product

### **Carcinogenicity**

Titanium Dioxide

The International Agency for Research on Cancer (IARC) has classified Titanium Dioxide as possibly carcinogenic to humans (Group 2B) based on inadequate evidence of carcinogenicity in humans and sufficient evidence of carcinogenicity in experimental animals

### Crystalline Silica

The International Agency for Research on Cancer (IARC) has classified inhaled crystalline silica (CAS No. 14808-60-7) as a Group 1 carcinogen based on sufficient evidence of carcinogenicity in humans and experimental animals. Exposure to inhaled crystalline silica can only occur when it is present in respirable form. Normal application procedures pose no hazard since the crystalline silica is wet and encapsulated, but grinding or sanding dried films of this product may yield respirable silica dusts.

### **Reproductive toxicity**

No information available on the product

### **Specific Target Organ Toxicity (STOT)-single exposure**

No information available on the product

### **Specific Target Organ Toxicity (STOT)-repeated exposure**

No information available on the product

### **Asphyxiation hazard**

May be harmful if swallowed and enters airways

---

## 12. ECOLOGICAL INFORMATION

---

### **Toxicity**

Aquatic toxicity -No data available

### **Persistence and degradability**

Biodegradation -No data available

### **Bioaccumulative potential**

No data available

### **Mobility in soil**

No data available

### **Result of PBT and vPvB assessment**

No data available

### **Other adverse effects**

There is no ecotoxicological test data available on the product itself.  
The product should not be allowed to enter drains or water courses.

---

## 13. DISPOSAL CONSIDERATIONS

---

The product should not be allowed to enter drains and watercourses.  
Preferred methods of waste disposal are incineration or biological treatment in federal/state approved facility. Empty containers should be recycled or disposed through an approved waste management facility or licensed contractor.  
All federal, state and local environmental regulations shall be observed.

---

## 14. TRANSPORT INFORMATION

---

Transport to be in accordance with ADR/RID for road/rail, IMDG for sea and IATA for Air.

### **LAND TRANSPORT**

Classified as Dangerous Goods by the criteria of the European Agreement concerning the international carriage of Dangerous Goods (ADR) by Road & Regulations concerning the international carriage of Dangerous goods (RID) by Rail.

UN Number: 1263  
Proper shipping name: PAINT (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base) or PAINT RELATED MATERIAL (including paint thinning or reducing compound)  
Class: 3  
Subsidiary Risk(s): -  
Packaging Group: III

#### **SEA TRANSPORT**

Classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport of Sea.

UN Number: 1263  
Proper shipping name: PAINT (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base) or PAINT RELATED MATERIAL (including paint thinning or reducing compound)  
Class: 3  
Subsidiary Risk(s): -  
Packaging Group: III  
Marine Pollutant No

#### **SEA (ANNEX II OF MARPOL 73/78 AND THE IBC CODE)**

Not applicable

#### **AIR TRANSPORT**

Classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for transport by Air

UN Number: 1263  
Proper shipping name: PAINT (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base) or PAINT RELATED MATERIAL (including paint thinning or reducing compound)  
Class: 3  
Subsidiary Risk(s): -  
Packaging Group: III

---

## **15. REGULATORY INFORMATION**

---

Applicable national regulations:

- Standards on Hazard communication for hazardous chemicals and dangerous goods
  - SS 586: Part 1: 2021-Transport and storage of dangerous goods
  - SS 586: Part 2: 2014-GHS of classification and labelling of chemicals
  - SS 586: Part 3: 2008(2014)-Preparation of safety data sheet
- MOM: Workplace Safety and Health Act & Workplace Safety and Health (General Provisions) Regulations
  - This product is subject to SDS, labelling, PEL and other requirements in the Acts/Regulations.
- NEA: Environmental Protection and Management Act & Environmental Protection and Management (Hazardous Substances) Regulations
  - This product is not subject to control under this Acts/Regulations.
- SCDF: Fire Safety Act & Fire Safety (Petroleum and Flammable Materials) Regulations



- This product is subject to the requirement of this Acts/Regulations.
  - SPF: The Arms and Explosive Act, the Arms and Explosives (Explosives) Rules, and the Arms and Explosives (Explosive Precursors) Rules
    - This product is not subject to the requirement of this Acts/Regulations.
- 

## 16. OTHER INFORMATION

---

Revision Date/Version No.: 08-02-2024 /3/2.3.3

History

Previous Revision Date /Version No.: 17-03-2023 /3/2.2.2

Abbreviation

ACGIH American Conference of Governmental Industrial Hygienists

TLV Threshold limit value

TWA Time-Weighted Average

OSHA Occupational Safety and Health Administration

PEL Permissible Exposure Limit

LD50 Lethal Dose

LC50 Median lethal concentration

IARC International Agency for Research in Cancer

Disclaimer

To the best of our knowledge, the information contained herein is accurate. However, the information is provided without any representation or warranty, expressed or implied, regarding its accuracy or completeness. Since the conditions of handling, storage, use and disposal are beyond our control and may be beyond our knowledge, for this and other reasons, we make no guarantee of results and assume no liability for damages incurred by the use of this product. Please be reminded that all chemicals may present unknown health hazards and should be used with caution.