

SAFETY DATA SHEET

SDS Number: SDS-70725 Version No: 003

Revision Date/Version No:08-02-2024 /3/4.2.2

1. IDENTIFICATION OF THE SUBSTANCE / MIXTURE AND OF THE COMPANY / UNDERTAKING

Product Name: HI-PON 80-18 HARDENER

Intended Use: Hardener for Paint

Manufacturer: Nippon Paint (S) Co. Pte Ltd

No. 1 First Lok Yang Road Jurong Singapore 629728

Emergency Phone Number: (65) 6 265 5355 Fax Numbers: (65) 6 264 1603

2. HAZARDS IDENTIFICATION

GHS Classification:

Physical Hazard

Not classified as a physical hazard under GHS criteria

Health Hazard

Acute Toxicity:

- Dermal Category 4
Skin corrosion/irritation Category 1
Serious eye damage/irritation Category 1
Skin sensitization Category 1
Reproductive toxicity Category 1

Environmental Hazard

Not classified as an environmental hazard under GHS criteria

GHS Pictogram



Signal Word

Danger

Hazard statements

H312: Harmful in contact with skin

H314: Causes severe skin burns and eye damage

H317: May cause an allergic skin reaction

H318: Causes serious eye damage

H360: May damage fertility or the unborn child

Precautionary statements

P201: Obtain special instructions before use

P202: Do not handle until all safety precautions have been read and understood

P260: Do not breathe dust/fume/gas/mist/vapours/spray

P261: Avoid breathing dust/fume/gas/mist/vapours/spray

P264: Wash hands thoroughly after handling

P272: Contaminated work clothing should not be allowed out of the workplace

P280: Wear protective gloves/protective clothing/eye protection/face protection

P281: Use personal protective equipment as required

Response

P310: Immediately call a POISON CENTER or doctor/physician

P312: Call a POISON CENTER or doctor/physician if you feel unwell

P321: Specific treatment (see Section 4 of SDS)

P322: Specific measures (see Section 4 of SDS)

P363: Wash contaminated clothing before reuse

P302+352: IF ON SKIN: Wash with soap and water

P304+340: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

P308+313: IF exposed or concerned: Get medical advice/attention

P333+313: If skin irritation or a rash occurs: Get medical advice/attention

P301+330+331: IF SWALLOWED: Rinse mouth. Do NOT induce vomiting

P303+361+353: IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower

P305+351+338: IF IN EYES: Rinse continuously with water for several minutes. Remove contact lenses if present and easy to do – continue rinsing

Storage

P405: Store locked up

Disposal

P501: Dispose of contents/container to appropriate waste site or reclaimer in accordance with local or national regulations

3. COMPOSITION / INFORMATION ON INGREDIENTS

Substances Triethylenetetramine	CAS No. 112-24-3	% 19-43
2-Propenenitril polymer mit 1,3-butadiene, 1-cyano-1-methyl-4-oxo-4- [[2-(1-piperazinyl)ethyl]amino]butyl-terminiert	68683-29-4	14-31
Methyleneoxide, polymer with benzenamine, hydrogenated	135108-88-2	3-8
m-Phenylenebis(methylamine)	1477-55-0	3-6
2-piperazin-1-ylethylamine	140-31-8	1-2
Substances determined to be non-hazardous	-	Balance
		100%

4. FIRST-AID MEASURES

INHALATION

- Move person to fresh air and call for medical assistance immediately.
- If not breathing, give artificial respiration, if breathing is difficult, give oxygen. Keep at rest.

SKIN CONTACT

- In case of contact, immediately flush skin with large amounts of water and soap while removing contaminated clothing and shoes.
- o If irritation persists, get medical attention.

EYE CONTACT

- o Immediately flush eyes with large amounts of water until irritation subsides.
- Remove contact lens.
- o Obtain medical attention, preferably by an ophthalmologist, immediately.

INGESTION

 DO NOT induce vomiting unless directed to do so by a medical personnel. Never give anything by mouth to an unconscious person. Keep at rest. Get medical attention immediately.

5. FIRE FIGHTING MEASURES

SUITABLE FIRE EXTINGUISHING MEDIA

Alcohol - resistant foam, Carbon dioxide, or dry chemical type.

SPECIFIC HAZARDS ARISING FROM THE CHEMICAL

 Combustion products may include and are not limited to: Carbon monoxide and Carbon dioxide.

SPECIAL PROTECTIVE ACTIONS FOR FIRE FIGHTERS

- Wear full protective clothing and NIOSH approved self contained breathing apparatus.
- Use water spray to cool fire exposed surfaces and to protect personnel. If a leak or spill has not ignited, use water spray to disperse the vapours.
- o If possible, isolate product from heat, electrical equipments, sparks and open flames.
- Avoid spraying water directly into storage containers.
- Closed containers may explode when exposed to extreme heat.
- Avoid spreading burning liquid with water, isolate liquid.
- o Do not allow runoff from fire fighting to enter drains or watercourses.

6. ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT AND EMERGENCY PROCEDURE

- Wear appropriate protective equipment, e.g. respirators, eye protection, gloves and safety shoes.
- Avoid substance contact with eyes. Do not inhale vapours.
- Ensure supply of fresh air in enclosed rooms.

ENVIRONMENTAL PRECAUTIONS

- Eliminate sources of ignition.
- Keep public away.
- Contain spilled liquid with sand or other non-combustible absorbent materials.
- Wash area and prevent runoff into drains and sewerage system.
- Advise authorities if substance has entered a watercourse or sewer or has contaminated soil or vegetation.

METHODS AND MATERIALS FOR CONTAINMENTS AND CLEANING UP

- Clean up all spills immediately.
- Absorb spill with absorbent and inert material, then place in container.
- Disposal in accordance to local/national regulations.

7. HANDLING AND STORAGE

PRECAUTIONS FOR SAFE HANDLING

- Use appropriate personal protective equipment
- Keep out of reach of children.
- Handle containers with care. Open slowly in order to control possible pressure release.
- Do not pressurize containers.
- Do not ingest. Do not breathe in gas/fumes/vapour. Avoid contact with skin and eyes.
- For personal protection, see section 8.
- Use only in areas from which all naked lights and other sources of ignition have been excluded.
- Take precautionary measures against static discharge
- Protect from frost and extremes of temperature

CONDITIONS FOR SAFE STORAGE, INCLUDING ANY INCOMPATIBILTIES

- Keep containers tightly closed
- o Containers that are opened should be properly resealed and kept upright to prevent leakage.
- Store in cool, dry and well ventilated place at temperature between 20°C to 40°C away from heat and sources of ignition

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

CONTROL PARAMETERS/OCCUPATIONAL LIMITS

Substances	ACGIH TLV-TWA		OSHA PEL-TWA	
	ppm	mg/m3	ppm	mg/m3
Triethylenetetramine	-	-	-	-
2-Propenenitril polymer mit 1,3-butadiene, 1-cyano-1-methyl-4-oxo-4- [[2-(1-piperazinyl)ethyl]amino]butyl-terminiert	-	-	-	-
Methyleneoxide, polymer with benzenamine, hydrogenated	-	-	-	-
m-Phenylenebis(methylamine)	-	-	-	-
2-piperazin-1-ylethylamine	_	_	_	_

APPROPRIATE ENGINEERING CONTROL MEASURES

- Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapours below their respective occupational exposure limits.
- Ensure eyewash stations and safety showers are close to the workstation location.

PERSONAL PROTECTION

Respiratory Protection: Use of NIOSH - approved respirators with organic vapour

cartridges is recommended.

Hand Protection: Use of solvent resistance type or chemical resistant type of

protective gloves is recommended.

Eye Protection: Use of safety glasses or goggles with side shields is

recommended.

Skin / Body Protection: Wear chemical resistant clothes and safety shoes when

handling product.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : Liquid

Odour : Aromatic hydrocarbon odour

Odour threshold : Not available pH : Not available Melting point/freezing point : Not available

Initial boiling point and boiling range : Between 203 and 266 °C

Flash point : 93 °C

Evaporation rate : Not available
Flammability (solid, gas) : Not applicable
Lower flammability or explosive limit : Not available
Upper flammability or explosive limit : Not available
Vapour pressure : Not available

Vapour density : > 1.00 (Vapour is heavier than air)

Relative density : Not available

Solubility : Not Miscible in water

Partition coefficient : Not available
Auto-ignition temperature : > 315 °C
Decomposition temperature : Not available
Viscosity : 84 - 88 KU

10. STABILITY AND REACTIVITY

REACTIVITY

o No dangerous reaction known under condition of normal use

CHEMICAL STABILITY

The product is stable under recommended storage and handling conditions. (see section7)

POSSIBILITY OF HAZARDOUS REACTION

Under normal conditions of storage and use, hazardous reaction will not occur

CONDITIONS TO AVOID

 Keep away from oxidising agents, strongly alkaline and strongly acidic materials in order to avoid exothermic reactions. Avoid all possible sources of ignition (spark or flame). Do not pressurize, cut, weld, braze, drill, grind or expose containers to heat or sources of ignition

HAZARDOUS DECOMPOSITION PRODUCTS

• When exposed to high temperatures may produce hazardous decomposition products such as carbon monoxide, carbon dioxide, oxides of nitrogen and smoke.

11. TOXICOLOGICAL INFORMATION

There is no data available on the product itself.

Toxicological information of substances:

Acute oral toxicity

Harmful if swallowed

Substances Oral LD50(Rat), mg/kg

Triethylenetetramine 2500

2-Propenenitril polymer mit 1,3-butadiene, 1-cyano-1-methyl-4-oxo-4- Data not available

[[2-(1-piperazinyl)ethyl]amino]butyl-terminiert

Methyleneoxide, polymer with benzenamine, hydrogenated 1200 m-Phenylenebis(methylamine) 930

2-piperazin-1-ylethylamine Data not available

Acute dermal/skin toxicity

May be harmful if in contact with skin

Substances Dermal LD50 (Rabbit), mg/kg

Triethylenetetramine 550

2-Propenenitril polymer mit 1,3-butadiene, 1-cyano-1-methyl-4-oxo-4- Data not available

[[2-(1-piperazinyl)ethyl]amino]butyl-terminiert

Methyleneoxide, polymer with benzenamine, hydrogenated 2000

m-Phenylenebis(methylamine)

2-piperazin-1-ylethylamine

Data not available

Data not available

Acute inhalation toxicity

Vapour concentrations above the recommended exposure levels may be irritating to the eyes and the respiratory tract, may cause headaches and dizziness, could be anesthetic and may have other central nervous system effects.

Substances Inhalation Vapor LC50 (Rat), mg/L/4hr

Triethylenetetramine Data not available 2-Propenenitril polymer mit 1,3-butadiene, 1-cyano-1-methyl-4-oxo-4- Data not available

[[2-(1-piperazinyl)ethyl]amino]butyl-terminiert

Methyleneoxide, polymer with benzenamine, hydrogenated Data not available m-Phenylenebis(methylamine) Data not available 2-piperazin-1-ylethylamine Data not available

Skin corrosion or irritation

Causes skin irritation. Frequent or prolonged contact may dry the skin, leading to discomfort and dermatitis.

Serious eye damage or irritation

May be an eye irritant

Respiratory or skin sensitisation

Vapour concentrations above the recommended exposure levels may be irritating to the eyes and the respiratory tract

Germ cell mutagenicity

No information available on the product

Carcinogenicity

No information available on the product

Reproductive toxicity

No information available on the product

Specific Target Organ Toxicity (STOT)-single exposure

No information available on the product

Specific Target Organ Toxicity (STOT)-repeated exposure

No information available on the product

Asphyxiation hazard

May be harmful if swallowed and enters airways

12. ECOLOGICAL INFORMATION

Toxicity

Aquatic toxicity -No data available

Persistence and degradability

Biodegradation -No data available

Bioaccumulative potential

No data available

Mobility in soil

No data available

Result of PBT and vPvB assessment

No data available

Other adverse effects

There is no ecotoxicological test data available on the product itself.

The product should not be allowed to enter drains or water courses.

13. DISPOSAL CONSIDERATIONS

The product should not be allowed to enter drains and watercourses.

Preferred methods of waste disposal are incineration or biological treatment in federal/state approved facility. Empty containers should be recycled or disposed through an approved waste management facility or licensed contractor.

All federal, state and local environmental regulations shall be observed.

14. TRANSPORT INFORMATION

Transport to be in accordance with ADR/RID for road/rail, IMDG for sea and IATA for Air.

LAND TRANSPORT

Classified as Dangerous Goods by the criteria of the European Agreement concerning the international carriage of Dangerous Goods (ADR) by Road & Regulations concerning the international carriage of Dangerous goods (RID) by Rail.

UN Number: 3066

Proper shipping name: PAINT (including paint, lacquer, enamel, stain, shellac, varnish,

polish, liquid filler and liquid lacquer base) or PAINT RELATED MATERIAL (including paint thinning or reducing compound)

Class: 8
Subsidary Risk(s): Packaging Group: II

SEA TRANSPORT

Classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport of Sea.

UN Number: 3066

Proper shipping name: PAINT (including paint, lacquer, enamel, stain, shellac, varnish,

polish, liquid filler and liquid lacquer base) or PAINT RELATED MATERIAL (including paint thinning or reducing compound)

Class: 8

Subsidary Risk(s): Packaging Group: II
Marine Pollutant No

SEA (ANNEX II OF MARPOL 73/78 AND THE IBC CODE)

Not applicable

AIR TRANSPORT

Classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for transport by Air

UN Number: 3066

Proper shipping name: PAINT (including paint, lacquer, enamel, stain, shellac, varnish,

polish, liquid filler and liquid lacquer base) or PAINT RELATED MATERIAL (including paint thinning or reducing compound)

Class: 8
Subsidary Risk(s): Packaging Group: II

15. REGULATORY INFORMATION

Applicable national regulations:

- Standards on Hazard communication for hazardous chemicals and dangerous goods
 - SS 586: Part 1: 2021-Transport and storage of dangerous goods
 - SS 586: Part 2: 2014-GHS of classification and labelling of chemicals
 - SS 586: Part 3: 2008(2014)-Preparation of safety data sheet
- MOM: Workplace Safety and Health Act & Workplace Safety and Health (General Provisions)
 Regulations
 - This product is subject to SDS, labelling, PEL and other requirements in the Acts/Regulations.
- NEA: Environmental Protection and Management Act & Environmental Protection and Management (Hazardous Substances) Regulations
 - This product is not subject to control under this Acts/Regulations.
- SCDF: Fire Safety Act & Fire Safety (Petroleum and Flammable Materials) Regulations
 - This product is subject to the requirement of this Acts/Regulations.
- SPF: The Arms and Explosive Act, the Arms and Explosives (Explosives) Rules, and the Arms and Explosives (Explosive Precursors) Rules
 - This product is not subject to the requirement of this Acts/Regulations.

16. OTHER INFORMATION

Revision Date/Version No.: 08-02-2024 /3/4.2.2

History

Previous Revision Date /Version No.: 05-04-2021 /3/4.1.1

Abbreviation

ACGIH American Conference of Governmental Industrial Hygienists

TLV Threshold limit value

TWA Time-Weighted Average

OSHA Occupational Safety and Health Administration

PEL Permissible Exposure Limit

LD50 Lethal Dose

LC50 Median lethal concentration

IARC International Agency for Research in Cancer

Disclaimer

To the best of our knowledge, the information contained herein is accurate. However, the information is provided without any representation or warranty, expressed or implied, regarding its accuracy or completeness. Since the conditions of handling, storage, use and disposal are beyond our control and may be beyond our knowledge, for this and other reasons, we make no guarantee of results and assume no liability for damages incurred by the use of this product. Please be reminded that all chemicals may present unknown health hazards and should be used with caution.