



SAFETY DATA SHEET

SDS Number: SDS-OTH-0279
Updated Date: 14/09/2023

Version 001

1. IDENTIFICATION OF THE SUBSTANCE / MIXTURE AND OF THE COMPANY / UNDERTAKING

Product Name:	PROOF-SEAL 2305 1K Polyurethane Root - Resistant Coating
Intended Use:	Waterproofing Coating
Supplier:	Nippon Paint (S) Co. Pte Ltd No. 1 First Lok Yang Road Jurong Singapore 629728
Emergency Phone Number:	(65) 6 265 5355
Fax Numbers:	(65) 6 264 1603

2. HAZARD IDENTIFICATION

GHS Classification:

Physical Hazard

Flammable Liquid Category 4

Health Hazard

Acute Toxicity:
-Inhalation Category 4
Skin corrosion/Irritation Category 3

Environment Hazard

Not classified as an environmental hazard under GHS criteria

GHS Pictogram



Signal Word

Warning

Hazard statements

H227: Combustible Liquid
H335: Causes mild skin irritation
H332: Harmful if inhaled

Precautionary statements

P210: Keep away from heat/sparks/open flames/hot surfaces – No smoking
P261: Avoid breathing dust/fume/gas/mist/vapours/spray
P271: Use only outdoors or in a well-ventilated area
P280: Wear protective gloves/protective clothing/eye protection/face protection
P332+313: If skin irritation occurs: Get medical advice/attention

Response

P312: Call a POISON CENTER or doctor/physician if you feel unwell

PROOF-SEAL 2305 1K Polyurethane Root-Resistant Coating

P304+340: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

P370+378: In case of fire: Use appropriate media for extinction

Storage

P403+235: Store in a well ventilated place. Keep cool

Disposal

P501: Dispose of content/container to appropriate waste site or reclaimer in accordance with local or national regulations

3. COMPOSITION / INFORMATION ON INGREDIENTS

<u>Ingredient</u>	<u>CAS No.</u>	<u>%</u>
Polyurethane Resin	9009-54-5	35
Chlorinated Paraffin	106232-86-4	16
Calcium Carbonate	117-81-7	25
Talc	14807-96-6	15
Solvent Naphtha	64742-95-6	9

4. FIRST-AID MEASURES

INHALATION

- Move person to fresh air and call for medical assistance immediately.
- If not breathing, give artificial respiration, if breathing is difficult, give oxygen. Keep at rest.

SKIN CONTACT

- In case of contact, immediately flush skin with large amounts of water and soap while removing contaminated clothing and shoes.
- If irritation persists, get medical attention.

EYE CONTACT

- Immediately flush eyes with large amounts of water until irritation subsides.
- Remove contact lens
- Obtain medical attention, preferably by an ophthalmologist, immediately.

INGESTION

- DO NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Keep at rest. Get medical attention immediately.

5. FIRE FIGHTING MEASURE

SUITABLE FIRE EXTINGUISHING MEDIA

- Alcohol-resistant foam, Carbon dioxide, or dry chemical type

SPECIFIC HAZARDS ARISING FROM THE CHEMICAL

- Combustion products may include and are not limited to: Carbon monoxide and Carbon dioxide.

SPECIAL PROTECTIVE ACTIONS FOR FIRE FIGHTERS

- Wear full protective clothing and NIOSH-approved self-contained breathing apparatus.
- Use water spray to cool fire-exposed surfaces and to protect personnel. If a leak or spill has not ignited, use water spray to disperse the vapours.
- If possible, isolate product from heat, electrical equipment, sparks and open flames.
- Avoid spraying water directly into storage containers.
- Closed containers may explode when exposed to extreme heat.
- Avoid spreading burning liquid with water, isolate liquid.
- Do not allow run-off from firefighting to enter drains or watercourses.

PROOF-SEAL 2305 1K Polyurethane Root-Resistant Coating

6. ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT AND EMERGENCY PROCEDURE

- Wear appropriate protective equipment, e.g., respirators, eye protection, gloves and safety shoes.
- Avoid substance contact with eyes. Do not inhale vapours.
- Ensure supply of fresh air in enclosed rooms.

ENVIRONMENTAL PRECAUTIONS

- Eliminate sources of ignition.
- Keep public away.
- Contain spilled liquid with sand or other non-combustible absorbent materials
- Wash area and prevent runoff into drains and sewerage system.
- Advise authorities if substance has entered a watercourse or sewer or has contaminated soil or vegetation.

METHODS AND MATERIALS FOR CONTAINMENTS AND CLEANING UP

- Clean up all spills immediately.
- Absorb spill with absorbent and inert material, then place in container.
- Disposal in accordance to local/national regulations.

7. HANDLING AND STORAGE

PRECAUTIONS FOR SAFE HANDLING

- Use appropriate personal protective equipment
- Keep out of reach of children.
- Handle containers with care. Open slowly in order to control possible pressure release.
- Do not pressurize containers.
- Do not ingest. Do not breathe in gas/fumes/vapour. Avoid contact with skin and eyes.
- For personal protection, see section 8.
- Use only in areas from which all naked lights and other sources of ignition have been excluded.
- Take precautionary measures against static discharge
- Protect from frost and extremes of temperature.

CONDITIONS FOR SAFE STORAGE, INCLUDING ANY INCOMPATIBILITIES

- Keep containers tightly closed.
- Containers that are opened should be properly resealed and kept upright to prevent leakage.
- Store in cool, dry and well-ventilated place at temperature between 20°C to 40°C away from heat and sources of ignition.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

CONTROL PARAMETERS/OCCUPATIONAL LIMITS

<u>Ingredient</u>	<u>ACGIH TLV-TWA</u>		<u>OSHA PEL-TWA</u>	
	<u>ppm</u>	<u>mg/m3</u>	<u>ppm</u>	<u>mg/m3</u>
Polyurethane Resin	-	-	-	-
Chlorinated Paraffin	-	-	-	-
Calcium Carbonate	-	-	-	15
Talc	-	2	20	-
Solvent Naphtha	-	-	-	-

APPROPRIATE ENGINEERING CONTROL MEASURES

- Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapours below their respective occupational exposure limits.
- Ensure eyewash stations and safety showers are close to the workstation location.

PERSONAL PROTECTION

PROOF-SEAL 2305 1K Polyurethane Root-Resistant Coating

Respiratory Protection:	Use of SS548 or NIOSH-approved respirators with organic vapour cartridges is recommended.
Hand Protection:	Use of solvent resistance type or chemical resistant type of protective gloves is recommended.
Eye Protection:	Use of SS473(Part 2) approved safety glasses or goggles with side shields is recommended.
Skin / Body Protection:	Wear chemical resistant clothes and SS 513 (Part 1) approved safety shoes when handling product.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	:	Black or Grey thick liquid
Odour	:	Aromatic odour
Odour threshold	:	Not available
pH	:	Not available
Melting point/freezing point	:	Not available
Initial boiling point and boiling range	:	Not available
Flash point	:	130°C
Evaporation rate	:	Not available
Flammability (solid, gas)	:	Not applicable
Lower flammability or explosive limit	:	Not available
Upper flammability or explosive limit	:	Not available
Vapour pressure	:	Not available
Vapour density	:	Not available
Relative density	:	1.45-1.55kg/L (25°C)
Solubility	:	Soluble in organic solvents
Partition coefficient	:	Not available
Auto-ignition temperature	:	Not available
Decomposition temperature	:	Not available
Viscosity	:	4000 – 12000 [25°C, mPa.s(cps)]

10. STABILITY AND REACTIVITY

REACTIVITY

- No dangerous reaction known under condition of normal use.

CHEMICAL STABILITY

- The product is stable under recommended storage and handling conditions. (See section 7)

POSSIBILITY OF HAZARDOUS REACTION

- Under normal conditions of storage and use, hazardous reaction will not occur.
- Containers may explode when heated

CONDITIONS TO AVOID

- Avoid all possible sources of ignition (spark or flame). Do not pressurize, cut, weld, braze, drill, grind or expose containers to heat or sources of ignition.

HAZARDOUS DECOMPOSITION PRODUCTS

- When exposed to high temperatures may produce hazardous decomposition products such as irritative, toxic and corrosive gases
-

11. TOXICOLOGICAL INFORMATION

There is no data available on the product itself.

Toxicological information of ingredients:

Acute Oral toxicity

Harmful if swallowed.

	<u>Oral LD50(Rat), mg/kg</u>
Polyurethane Resin	Data not available

PROOF-SEAL 2305 1K Polyurethane Root-Resistant Coating

Chlorinated Paraffin	Data not available
Calcium Carbonate	Data not available
Talc	Data not available
Solvent Naphtha	Data not available

Acute dermal/skin toxicity

May be harmful if in contact with skin

	<u>Dermal LD50 (Rabbit), mg/kg</u>
Polyurethane Resin	Data not available
Chlorinated Paraffin	Data not available
Calcium Carbonate	Data not available
Talc	Data not available
Solvent Naphtha	Data not available

Acute inhalation toxicity

Vapour concentrations above the recommended exposure levels may be irritating to the eyes and the respiratory tract, may cause headaches and dizziness, could be anesthetic and may have other central nervous system effects.

	<u>Inhalation Vapor (Rat) LC50, mg/L/4hr</u>
Polyurethane Resin	Data not available
Chlorinated Paraffin	Data not available
Calcium Carbonate	Data not available
Talc	Data not available
Solvent Naphtha	Data not available

Skin corrosion or irritation

Causes skin irritation. Frequent or prolonged contact may dry the skin, leading to discomfort and dermatitis.

Serious eye damage or irritation

May be an eye irritant.

Respiratory or skin sensitization

Vapour concentrations above the recommended exposure levels may be irritating to the eyes and the respiratory tract,

Germ cell mutagenicity

No information available on the product.

Carcinogenicity

No information available on the product.

Reproductive toxicity

No information available on the product.

Specific Target Organ Toxicity (STOT)- single exposure

No information available on the product.

Specific Target Organ Toxicity (STOT)- repeated exposure

No information available on the product.

Aspiration hazard

No information available on the product.

12. ECOLOGICAL INFORMATION

Toxicity

Aquatic toxicity -No data available

PROOF-SEAL 2305 1K Polyurethane Root-Resistant Coating

Persistence and degradability

Biodegradation -No data available

Bioaccumulative potential

-No data available

Mobility in soil

-No data available

Result of PBT and vPvB assessment

-No data available

Other adverse effects

There is no ecotoxicological test data available on the product itself.

The product should not be allowed to enter drains or water courses

13. DISPOSAL CONSIDERATIONS

The product should not be allowed to enter drains and watercourses.

Preferred methods of waste disposal are incineration or biological treatment in federal/state approved facility. Empty containers should be recycled or disposed through an approved waste management facility or licensed contractor.

All federal, state and local environmental regulations shall be observed.

14. TRANSPORT INFORMATION

Transport to be in accordance with ADR/RID for road, IMDG for sea and IATA for Air.

LAND TRANSPORT

Not classified as Dangerous Goods by the criteria of the European Agreement concerning the international carriage of Dangerous Goods (ADR) by Road & Regulations concerning the international carriage of Dangerous goods (RID) by Rail.

SEA TRANSPORT

Not classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport of Sea.

SEA (Annex II of MARPOL 73/78 and the IBC code)

Not applicable

AIR TRANSPORT

Not classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for transport by Air

15. REGULATORY INFORMATION

Applicable national regulations:

- Standards on Hazard communication for hazardous chemicals and dangerous goods
 - SS 586: Part 1: 2021- Transport and storage of dangerous goods
 - SS 586: Part 2: 2014- GHS of classification and labelling of chemicals- Singapore's adaptations
 - SS 586: Part 3: 2008- Preparation of safety data sheets (SDS)
- MOM: Workplace Safety and Health Act & Workplace Safety and Health (General Provisions) Regulations
 - This product is subject to SDS, labelling, PEL and other requirements in the Acts/Regulations

- NEA: Environmental Protection and Management Act & Environmental Protection and Management (Hazardous Substances) Regulations.
 - This product is not subject to control under this Acts/Regulations
- SCDF: Fire Safety Act & Fire Safety (Petroleum and Flammable Materials) Regulations
 - This product is not subject to the requirement of this Acts/Regulations
- SPF: The Arms and Explosive Act, the Arms and Explosives (Explosives) Rules, and the Arms and Explosives (Explosive Precursors) Rules
 - This product is not subject to the requirement of this Acts/Regulations

16. OTHER INFORMATION

Revision date: 14/09/2023

Abbreviation

ACGIH American Conference of Governmental Industrial Hygienists

TLV Threshold limit value

TWA Time-Weighted Average

OSHA Occupational Safety and Health Administration

PEL Permissible Exposure Limit

LD50 Lethal Dose

LC50 Median lethal concentration

IARC International Agency for Research in Cancer

To the best of our knowledge, the information contained herein is accurate. However, the information is provided without any representation or warranty, expressed or implied, regarding its accuracy or completeness. Since the conditions of handling, storage, use and disposal are beyond our control and may be beyond our knowledge, for this and other reasons, we make no guarantee of results and assume no liability for damages incurred by the use of this product. Please be reminded that all chemicals may present unknown health hazards and should be used with caution.