

TECHNICAL DATA SHEET FOR

SOLARCOOL

DESCRIPTION	: SolarCool is a cool coating that satisfies SS 678:2021 specification for solar reflective water-based coatings. It offers superior weathering & algae resistant in attractive low sheen finishing. Using COOL-TEC Technology, SolarCool reflects strongly in solar radiation and reduces heat absorption effectively, keeping buildings cool
TYPE	: 100% acrylic polymer
COLOUR	: As per colour card
FINISH	: Low Sheen
USES	: <ul style="list-style-type: none">• Exterior coating system for use on masonry wall surfaces such as concrete, cement plastered wall and brickwork.
FEATURES	: <ul style="list-style-type: none">• Excellent weather resistance• Excellent resistance to fungal and algal growth• Excellent dirt pick-up resistance• Excellent resistance to alkaline and efflorescence• Long lasting colours• Non-toxic, does not contain lead, mercury and heavy metals• Environmentally friendly paint certified under the Singapore Green Building Product Certification Scheme, Solar reflective paint category
APPLICATION DATA	
METHOD	: Roller, brush, airless spray or air spray
RECOMMENDED APPLICATION THICKNESS	: 30 – 40 microns DFT
THEORETICAL COVERAGE	: Approximately 10 m ² / litre based on maximum 40 microns DFT (Actual coverage is dependent on substrate porosity and surface condition)
DILUTION	: No dilution is necessary for best performance

SOLARCOOL

SURFACE PREPARATION : Ensure surface is clean, dry and stable using the following suggested surface treatments:

- **Moisture:** There must not be any water residue on the surface of the substrate. Moisture must be <4% (Sovereign moisture master) before application
- **Unstable matter:** Remove loose bonding film, dirt, peeling paint, etc by high-pressure water jet wash or mechanical means such as power brush or scraper, whichever is suitable
- **Contaminants:** Remove dust and foreign matter by cleaning with damp cloth. Remove oil or grease using solvent or mild detergent. Allow surface to dry
- **Fungus and Algae:** Wash the affected area to remove unstable matters and micro-organisms. Apply Anti-Fungus Solution and leave on for at least 2 hours
- **Hairline cracks:** Fill cracks with suitable exterior grade water-resistant putty or filler

DRYING TIME : Touch Dry - 30 minutes at 30 °C
Hard Dry - 1 hour at 30 °C

OVERCOATING TIME : 2 hours minimum in normal conditions

RECOMMENDED PAINTING SYSTEM : 1 coat of SolaReflect Sealer-Primer White or Vinilex 2000 Wall Sealer
2 coats of SOLARCOOL

Powdery substrate is recommended to apply Vinilex 5170 oil-based sealer follow by the above painting system

CLEANING : All equipments should be cleaned with water immediately after use

GENERAL INFORMATION

SOLID CONTENT : 54.0 ± 2.0 % by weight (based on white colour)

DENSITY : 1.35 ± 2.0 % kg / litre (based on white colour)

PACKING : 20 litres

STORAGE : Store in a tightly sealed container in a cool, dry place

SHELF LIFE : Up to 24 months in a tightly sealed container

PRECAUTION : Ensure good ventilation during application and drying of paint. Avoid direct contact with sensitive skin. Use appropriate personal protective equipment

Refer to the product Safety Data Sheet for more information

The information given is intended to give a description of the product performance under specific test conditions. Nevertheless, we cannot assume any responsibility for the use of it since circumstances under which the products are applied in practice are subjected to many variations. We reserve the right to alter the given data without notice.

Enquiries / Contact Details : **Customer Service**
6265 5355 (Main Line)
6264 1603 (Fax)
www.nipponpaint.com.sg