

**TECHNICAL DATA SHEET FOR
EASYWASH SUPREME**

DESCRIPTION	:	EasyWash Supreme is a premium interior paint designed to protect against fungus and mould growth. Its elegant low-sheen finish creates a durable surface that resists common household marks and stains while ensuring long-lasting colour retention.
TYPE	:	Acrylic polymer emulsion
COLOUR	:	As per color card
FINISH	:	Low sheen
USES	:	It is suitable on all interior masonry surfaces and ideal for use in areas with high human traffic such as hallways and living areas.
FEATURES	:	<ul style="list-style-type: none">• Excellent stain resistance• Excellent washability• Resistance to alkali• Low odour• Low VOC• Mould & fungus resistant• Excellent flow and levelling• Excellent coverage and hiding power• Free from Alkylphenol Ethoxylate (APEO) & formaldehyde• Does not contain lead, mercury and heavy metals• Environmentally friendly paint certified under the Singapore Green Building Product Certification Scheme

APPLICATION DATA

METHOD	:	Roller or brush
THEORETICAL COVERAGE	:	13 m ² / litre (30 microns DFT)
DILUTION	:	No dilution is necessary for best performance
SURFACE PREPARATION	:	Ensure surface is clean, dry and stable using the following suggested surface treatments: <ul style="list-style-type: none">• Moisture: There must not be any water residue on the surface of the substrate. Moisture must be <4% (Sovereign moisture master) before application

EASYWASH SUPREME

- SURFACE PREPARATION** :
- **Unstable matter:** Remove loose bonding film, dirt, peeling paint, etc by high-pressure water jet wash or mechanical means such as power brush or scraper, whichever is suitable
 - **Contaminants:** Remove dust and foreign matter by cleaning with damp cloth. Remove oil or grease using solvent or mild detergent. Allow surface to dry
 - **Fungus and Algae:** Wash the affected area to remove unstable matters and micro-organisms. Apply Anti-Fungus Solution and leave on for at least 2 hours
 - **Hairline cracks:** Fill cracks with suitable exterior grade water-resistant putty or filler

DRYING TIME :

Surface Dry	: 30 minutes at 30 °C
Hard Dry	: 2 hours at 30 °C

OVERCOATING TIME : 2 hours minimum based on normal conditions

RECOMMENDED PAINTING SYSTEM : 1 coat 5101 Odour-less Sealer
2 coats EasyWash Supreme

CLEANING : All equipments should be cleaned with water immediately after use

GENERAL INFORMATION

SOLID CONTENT : 54.0 ± 2.0 % by weight (based on white colour)

SPECIFIC GRAVITY : 1.37 ± 2.0 % (based on white colour)

PACKING : 1 litres and 5 litres

STORAGE : Store in a tightly sealed container in a cool, dry place

SHELF LIFE : Up to 24 months in a tightly sealed container

PRECAUTION : Ensure good ventilation during application and drying of paint. Avoid direct contact with sensitive skin. Use appropriate personal protective equipment
Refer to the product Safety Data Sheet for more information

The information given is intended to give a description of the product performance under specific test conditions. Nevertheless, we cannot assume any responsibility for the use of it since circumstances under which the products are applied in practice are subjected to many variations. We reserve the right to alter the given data without notice.

Enquiries / Contact Details : **Customer Service**
6265 5355 (Main Line)
www.nipponpaint.com.sg